


Product specification

Date: 2019-06-14 Index: 1



**Preiss-Daimler
FibreGlass AB**

Installation steps



Product: Gjøco Proff Vegg 8931P25

Description: Precoated Glass wall liner for indoor walls and ceilings.

Composition: 10 micron fibers.
Double sided precoated Termoset coating

Technical data:



Properties	Unit	Min value	Nom value	Max value
Width	mm	997	1000	1003
Length deviation	m	-0		
Thickness	mm		0,4	
Total weight	g / m ²	72	80	88
<u>Tensile strength</u>				
MD	N / 5cm	230	275	
CD	N / 5cm	170	200	

Glue consumption See instructions on the glue bucket.

Paint consumption First coating Second coating
m² / litre 4,3 9

Facing side

Facing side is the outside of the roll.



Reverse side marking

Grey ink print 23 cm from the rolls edge.

Pattern matching

Free match




Allowed amount of marked spot faults

Roll length 15m Max 1
Roll length 25 & 30m Max 2
Roll length 50m Max 3

Note: A joint can occur in a roll and is considered as a spot fault.

Certificates:



Storing: -10 to +50 degrees Celcius
Use within 2 years after production

Information above is accurate to the best of our knowledge. Our products are subject to rigorous quality control along the production line to ensure conformance. Divergence within our tolerance may occur.

Preiss-Daimler FibreGlass AB, Box 7013, S-250 07 Helsingborg. Tel +46 42 25 05 00, Fax + 46 42 16 01 42

