

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1. Product identifier

<b>Trade name or designation of the mixture</b>	COLTEC™ C US-N
<b>Registration number</b>	-
<b>Synonyms</b>	None.
<b>SAP Specification</b>	000000051769
<b>Issue date</b>	05-July-2018
<b>Version number</b>	01

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

<b>Identified uses</b>	Colorants for tinting of paints / coatings.
<b>Uses advised against</b>	None known.

### 1.3. Details of the supplier of the safety data sheet

<b>Company</b>	Chromaflo Technologies B.V. P.O. Box 1076, 6201BB Maastricht NL-6222 NL Maastricht, The Netherlands
----------------	---

<b>Company</b>	Chromaflo Technologies Europe B.V. Nusterweg 98, 6136 KV Sittard, The Netherlands
----------------	--

<b>Telephone</b>	+31 (0)43 352-7700
<b>Telefax</b>	+31 (0)43 362-2238
<b>Email address</b>	EHS_EMEA@CHROMAFLO.COM

**GLOBAL EMERGENCY NUMBER** +1-760-476-3961

**ACCESS CODE** 334294

**CONTRACT Number** 12154

**General in EU** 112 (Available 24 hours a day. SDS/Product information may not be available for the Emergency Service.)

**Austria National Poisons Information Center** +431 406 4343 (Available 24 hours a day. SDS/Product information may not be available for the Emergency Service.)

**Belgium National Poisons Control Center** 070 245 245 (Available 24 hours a day. SDS/Product information may not be available for the Emergency Service.)

**Bulgaria National Toxicological Information Center** +359 2 9154 409 (Available 24 hours a day. SDS/Product information may not be available for the Emergency Service.)

**Czech Republic National Poisons Information Center** +420 224 919 293, or +420 224 915 402 (Hours of operation not provided. SDS/Product information may not be available for the Emergency Service.)

**Denmark National Poisons Control Center** +45 82 12 12 12 (Available 24 hours a day. SDS/Product information may not be available for the Emergency Service.)

**Estonia National Poisons Information Center** 16662 or abroad: (+372) 626 9390 (Monday 9:00AM to Saturday 9:00AM (closed on Sundays and on national holidays). SDS/Product information may not be available for the Emergency Service.)

**Finland National Poison Information Center** (09) 471 977 (direct) or (09) 4711 (exchange) (Available 24 hours a day. SDS/Product information may not be available for the Emergency Service.)

**France National Poisons Control Center** ORFILA number (INRS): + 33 (0) 1 45 42 59 59 (Available 24 hours a day. SDS/Product information may not be available for the Emergency Service.)

**Hungary National Emergency Phone Number** 36 80 20 11 99 (Available 24 hours a day. SDS/Product information may not be available for the Emergency Service.)

<b>Lithuania Neatidéliotina informacija apsinuodijus</b>	+370 5 236 20 52 or +37068753378 (Hours of operation not provided. SDS/Product information may not be available for the Emergency Service.)
<b>Malta Accident and Emergency Department</b>	2545 4030 (Hours of operation not provided. SDS/Product information may not be available for the Emergency Service.)
<b>Netherlands National Poisons Information Center (NVIC)</b>	030-274 88 88 (Only for the purpose of informing medical personnel in cases of acute intoxications)
<b>Norway Norwegian Poison Information Center</b>	22 59 13 00 (Available 24 hours a day. SDS/Product information may not be available for the Emergency Service.)
<b>Portugal Centro de Informacao Antivenenos</b>	(+351) 808 250 143 (Available 24 hours a day. SDS/Product information may not be available for the Emergency Service.)
<b>Romania Biroul RSI si Informare Toxicologica</b>	021.318.36.06 (Available 8:00AM-3:00PM. SDS/Product information may not be available for the Emergency Service.)
<b>Slovakia National Toxicological Information Center</b>	+421 2 5477 4166 (Available 24 hours a day. SDS/Product information may not be available for the Emergency Service.)
<b>Sweden National Poison Information Center</b>	112 - and ask for Poison Information (Available 24 hours a day. SDS/Product information may not be available for the Emergency Service.)

## SECTION 2: Hazards identification

### 2.1. Classification of the substance or mixture

The mixture has been assessed and/or tested for its physical, health and environmental hazards and the following classification applies.

#### Classification according to Regulation (EC) No 1272/2008 as amended

This mixture does not meet the criteria for classification according to Regulation (EC) 1272/2008 as amended.

#### Hazard summary

Prolonged exposure may cause chronic effects. Not classified for health hazards. However, occupational exposure to the mixture or substance(s) may cause adverse health effects. If product is in liquid or paste form, physical or health hazards listed related to dust are not considered significant. However, product may contain substances that could be potential hazards if caused to become airborne due to grinding, sanding or other abrasive processes.

### 2.2. Label elements

#### Label according to Regulation (EC) No. 1272/2008 as amended

<b>Hazard pictograms</b>	None.
<b>Signal word</b>	None.
<b>Hazard statements</b>	The mixture does not meet the criteria for classification.

#### Precautionary statements

<b>Prevention</b>	Observe good industrial hygiene practices.
<b>Response</b>	Wash hands after handling.
<b>Storage</b>	Store away from incompatible materials.
<b>Disposal</b>	Dispose of waste and residues in accordance with local authority requirements.

#### Supplemental label information

EUH208 - Contains 1,2-Benzisothiazol-3(2H)-one, 2-octyl-2h-isothiazol-3-one, Mixture of: 5-chloro-2-methyl-2H-isothiazol-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1). May produce an allergic reaction.

### 2.3. Other hazards

Not a PBT or vPvB substance or mixture.

## SECTION 3: Composition/information on ingredients

### 3.2. Mixtures

#### General information

Chemical name	%	CAS-No. / EC No.	REACH Registration No.	INDEX No.	Notes
1-Propanaminium, 3-amino-N-(carboxymethyl)-N,N-dimethyl-, N-(C8-18 and C18-unsatd. acyl) derivs., hydroxides, inner salts	1 - < 4	N/A 931-333-8	01-2119489410-39-XXXX	-	
<b>Classification:</b>	Eye Dam. 1;H318, Aquatic Chronic 3;H412				
1,2-Benzisothiazol-3(2H)-one	< 0,1	2634-33-5 220-120-9	-	613-088-00-6	M=1
<b>Classification:</b>	Acute Tox. 4;H302, Skin Irrit. 2;H315, Skin Sens. 1;H317, Eye Dam. 1;H318, Aquatic Acute 1;H400, Aquatic Chronic 2;H411				

Chemical name	%	CAS-No. / EC No.	REACH Registration No.	INDEX No.	Notes
2-octyl-2h-isothiazol-3-one	< 0,1	26530-20-1 247-761-7	-	613-112-00-5	
<b>Classification:</b>	Acute Tox. 4;H302, Acute Tox. 3;H311, Skin Corr. 1B;H314, Skin Sens. 1A;H317, Eye Dam. 1;H318, Acute Tox. 3;H331, Aquatic Acute 1;H400, Aquatic Chronic 1;H410				
Mixture of: 5-chloro-2-methyl-2H-isothiazol-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1)	< 0,1	55965-84-9	-	613-167-00-5	M=100
<b>Classification:</b>	Acute Tox. 3;H301, Acute Tox. 1;H310, Skin Corr. 1B;H314, Skin Sens. 1A;H317, Eye Dam. 1;H318, Acute Tox. 1;H330, Aquatic Acute 1;H400, Aquatic Chronic 1;H410				
Other components below reportable levels	90 - 100				

#### List of abbreviations and symbols that may be used above

#: This substance has been assigned Union workplace exposure limit(s).

M: M-factor

PBT: persistent, bioaccumulative and toxic substance.

vPvB: very persistent and very bioaccumulative substance.

All concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

#### Composition comments

The full text for all H-statements is displayed in section 16.

Specific Concentration Limit of 1-Propanaminium, 3-amino-N-(carboxymethyl)-N,N-dimethyl-, N-(C8-18 and C18-unsatd. acyl) derivs., inner salts  
Eye Dam. 1: > 10 %  
Eye Irrit. 2: > 4 - 10 %

## SECTION 4: First aid measures

#### General information

Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.

#### 4.1. Description of first aid measures

##### Inhalation

Move to fresh air. Call a physician if symptoms develop or persist.

##### Skin contact

Wash off with soap and water. Get medical attention if irritation develops and persists.

##### Eye contact

Rinse with water. Get medical attention if irritation develops and persists.

##### Ingestion

Rinse mouth. Get medical attention if symptoms occur.

#### 4.2. Most important symptoms and effects, both acute and delayed

Exposure may cause temporary irritation, redness, or discomfort.

#### 4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

## SECTION 5: Firefighting measures

#### General fire hazards

No unusual fire or explosion hazards noted.

#### 5.1. Extinguishing media

##### Suitable extinguishing media

Water fog. Foam. Dry chemical powder. Carbon dioxide (CO<sub>2</sub>).

##### Unsuitable extinguishing media

Do not use water jet as an extinguisher, as this will spread the fire.

#### 5.2. Special hazards arising from the substance or mixture

During fire, gases hazardous to health may be formed.

#### 5.3. Advice for firefighters

##### Special protective equipment for firefighters

Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

##### Special fire fighting procedures

Move containers from fire area if you can do so without risk.

#### Specific methods

Use standard firefighting procedures and consider the hazards of other involved materials.

## SECTION 6: Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

##### For non-emergency personnel

Keep unnecessary personnel away. For personal protection, see section 8 of the SDS.

**For emergency responders** Keep unnecessary personnel away. Use personal protection recommended in Section 8 of the SDS.

**6.2. Environmental precautions** Avoid discharge into drains, water courses or onto the ground.

**6.3. Methods and material for containment and cleaning up** Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Never return spills to original containers for re-use.

**6.4. Reference to other sections** For personal protection, see section 8 of the SDS. For waste disposal, see section 13 of the SDS.

## SECTION 7: Handling and storage

**7.1. Precautions for safe handling** Avoid prolonged exposure. Observe good industrial hygiene practices.

**7.2. Conditions for safe storage, including any incompatibilities** Store in original tightly closed container. Store away from incompatible materials (see Section 10 of the SDS).

**7.3. Specific end use(s)** Not available.

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

#### Occupational exposure limits

##### Austria. MAK List, OEL Ordinance (GwV), BGBl. II, no. 184/2001

Components	Type	Value	Form
2-octyl-2h-isothiazol-3-one (CAS 26530-20-1)	Ceiling	0,05 mg/m3	Inhalable fraction.
Mixture of: 5-chloro-2-methyl-2H-isothiazol-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1) (CAS 55965-84-9)	MAK	0,05 mg/m3	Inhalable fraction.
	MAK	0,05 mg/m3	
Poly (ethylene oxide) (CAS 25322-68-3)	MAK	1000 mg/m3	Inhalable fraction.
Talc (CAS 14807-96-6)	STEL	4000 mg/m3	Inhalable fraction.
	MAK	2 mg/m3	Respirable fraction.

##### Belgium. Exposure Limit Values.

Components	Type	Value	Form
aluminium silicate (CAS 1332-58-7)	TWA	2 mg/m3	Respirable fraction.
Talc (CAS 14807-96-6)	TWA	2 mg/m3	

##### Bulgaria. OELs. Regulation No 13 on protection of workers against risks of exposure to chemical agents at work

Components	Type	Value	Form
aluminium silicate (CAS 1332-58-7)	TWA	6 mg/m3	Inhalable fraction.
		3 mg/m3	Respirable fraction.
		1 fibers/cm3	Respirable fraction.
Talc (CAS 14807-96-6)	TWA	6 mg/m3	Inhalable fraction.
		3 mg/m3	Respirable fraction.
Trimethylolpropane (CAS 77-99-6)	TWA	50 mg/m3	

##### Croatia. Dangerous Substance Exposure Limit Values in the Workplace (ELVs), Annexes 1 and 2, Narodne Novine, 13/09

Components	Type	Value	Form
aluminium silicate (CAS 1332-58-7)	MAC	2 mg/m3	Respirable dust.
Talc (CAS 14807-96-6)	MAC	1 mg/m3	Respirable dust.

##### Cyprus. OELs. Control of factory atmosphere and dangerous substances in factories regulation, PI 311/73, as amended.

Components	Type	Value	Form
Talc (CAS 14807-96-6)	TWA	706 part/cm3	

**Czech Republic. OELs. Government Decree 361**

Components	Type	Value	Form
aluminium silicate (CAS 1332-58-7)	TWA	5 mg/m <sup>3</sup>	Dust.
Talc (CAS 14807-96-6)	TWA	10 mg/m <sup>3</sup> 10 mg/m <sup>3</sup>	Total dust. Respirable dust.

**Denmark. Exposure Limit Values**

Components	Type	Value	Form
aluminium silicate (CAS 1332-58-7)	TLV	2 mg/m <sup>3</sup>	Respirable.
Poly (ethylene oxide) (CAS 25322-68-3)	TLV	1000 mg/m <sup>3</sup>	

**Estonia. OELs. Occupational Exposure Limits of Hazardous Substances. (Annex of Regulation No. 293 of 18 September 2001)**

Components	Type	Value	Form
aluminium silicate (CAS 1332-58-7)	TWA	5 mg/m <sup>3</sup>	Respirable dust.
		10 mg/m <sup>3</sup>	Total dust.
		1 mg/m <sup>3</sup>	Dust.
Talc (CAS 14807-96-6)	TWA	5 mg/m <sup>3</sup> 10 mg/m <sup>3</sup> 1 mg/m <sup>3</sup>	Respirable dust. Total dust. Dust.

**Finland. Workplace Exposure Limits**

Components	Type	Value	Form
aluminium silicate (CAS 1332-58-7)	TWA	2 mg/m <sup>3</sup>	Respirable.
Talc (CAS 14807-96-6)	STEL	2 ppm 1 ppm	Inhalable dust. Respirable.

**France. Threshold Limit Values (VLEP) for Occupational Exposure to Chemicals in France, INRS ED 984**

Components	Type	Value	Form
aluminium silicate (CAS 1332-58-7)	VME	5 mg/m <sup>3</sup>	Respirable fraction.
		10 mg/m <sup>3</sup> 10 mg/m <sup>3</sup>	
Talc (CAS 14807-96-6)	VME	5 mg/m <sup>3</sup> 10 mg/m <sup>3</sup>	Inhalable fraction. Respirable fraction. Inhalable fraction.

**Germany. DFG MAK List (advisory OELs). Commission for the Investigation of Health Hazards of Chemical Compounds in the Work Area (DFG)**

Components	Type	Value	Form
2-octyl-2h-isothiazol-3-one (CAS 26530-20-1)	TWA	0,05 mg/m <sup>3</sup>	Inhalable fraction.
aluminium silicate (CAS 1332-58-7)	TWA	4 mg/m <sup>3</sup>	Inhalable dust.
Mixture of: 5-chloro-2-methyl-2H-isothiazol-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1) (CAS 55965-84-9)	TWA	0,3 mg/m <sup>3</sup> 0,2 mg/m <sup>3</sup>	Respirable dust. Inhalable fraction.
Talc (CAS 14807-96-6)	TWA	4 mg/m <sup>3</sup> 0,3 mg/m <sup>3</sup>	Inhalable dust. Respirable dust.

**Germany. TRGS 900, Limit Values in the Ambient Air at the Workplace**

Components	Type	Value	Form
2-octyl-2h-isothiazol-3-one (CAS 26530-20-1)	AGW	0,05 mg/m <sup>3</sup>	Inhalable fraction.
aluminium silicate (CAS 1332-58-7)	AGW	10 mg/m <sup>3</sup>	Inhalable fraction.
		1,25 mg/m <sup>3</sup>	Respirable fraction.
Poly (ethylene oxide) (CAS 25322-68-3)	AGW	1000 mg/m <sup>3</sup>	Inhalable fraction.
Talc (CAS 14807-96-6)	AGW	10 mg/m <sup>3</sup>	Inhalable fraction.

**Germany. TRGS 900, Limit Values in the Ambient Air at the Workplace**

Components	Type	Value	Form
		1,25 mg/m3	Respirable fraction.

**Greece. OELs (Decree No. 90/1999, as amended)**

Components	Type	Value	Form
Talc (CAS 14807-96-6)	TWA	2 mg/m3 10 mg/m3	Respirable. Inhalable

**Hungary. OELs. Joint Decree on Chemical Safety of Workplaces**

Components	Type	Value	Form
aluminium silicate (CAS 1332-58-7)	TWA	6 mg/m3	Respirable dust.
Talc (CAS 14807-96-6)	TWA	10 mg/m3 2 mg/m3	Total inhalable dust. Respirable.

**Iceland. OELs. Regulation 154/1999 on occupational exposure limits**

Components	Type	Value	Form
aluminium silicate (CAS 1332-58-7)	TWA	2 mg/m3	Respirable dust.
Talc (CAS 14807-96-6)	TWA	5 mg/m3 10 mg/m3	Respirable dust. Total dust.

**Ireland. Occupational Exposure Limits**

Components	Type	Value	Form
aluminium silicate (CAS 1332-58-7)	TWA	2 mg/m3	Respirable dust.
Talc (CAS 14807-96-6)	TWA	10 mg/m3 0,8 mg/m3	Total inhalable dust. Respirable dust.

**Italy. Occupational Exposure Limits**

Components	Type	Value	Form
aluminium silicate (CAS 1332-58-7)	TWA	2 mg/m3	Respirable fraction.
Talc (CAS 14807-96-6)	TWA	2 mg/m3	Respirable fraction.

**Latvia. OELs. Occupational exposure limit values of chemical substances in work environment**

Components	Type	Value	Form
aluminium silicate (CAS 1332-58-7)	TWA	2 mg/m3	Dust.
Talc (CAS 14807-96-6)	TWA	2 mg/m3 2 mg/m3 2 mg/m3	Dust.

**Lithuania. OELs. Limit Values for Chemical Substances, General Requirements**

Components	Type	Value	Form
aluminium silicate (CAS 1332-58-7)	TWA	5 mg/m3	Respirable fraction.
Talc (CAS 14807-96-6)	TWA	10 mg/m3 1 mg/m3 2 mg/m3 1 mg/m3	Inhalable fraction. Dust. Inhalable fraction. Respirable fraction.
Trimethylolpropane (CAS 77-99-6)	Ceiling	5 ppm	

**Netherlands. OELs (binding)**

Components	Type	Value	Form
Talc (CAS 14807-96-6)	TWA	0,25 mg/m3	Respirable dust.

**Norway. Administrative Norms for Contaminants in the Workplace**

Components	Type	Value	Form
aluminium silicate (CAS 1332-58-7)	TLV	5 mg/m3	Respirable dust.
Talc (CAS 14807-96-6)	TLV	10 mg/m3 6 mg/m3 2 mg/m3	Total dust. Total dust. Respirable dust.

**Poland. MACs. Minister of Labour and Social Policy Regarding Maximum Allowable Concentrations and Intensities in Working Environment**

Components	Type	Value	Form
aluminium silicate (CAS 1332-58-7)	TWA	10 mg/m3	Inhalable fraction.
Talc (CAS 14807-96-6)	TWA	4 mg/m3 1 mg/m3	Inhalable fraction. Respirable fraction.

**Portugal. VLEs. Norm on occupational exposure to chemical agents (NP 1796)**

Components	Type	Value	Form
aluminium silicate (CAS 1332-58-7)	TWA	2 mg/m3	Respirable fraction.
Talc (CAS 14807-96-6)	TWA	2 mg/m3	Respirable fraction.

**Romania. OELs. Protection of workers from exposure to chemical agents at the workplace**

Components	Type	Value	Form
aluminium silicate (CAS 1332-58-7)	TWA	2 mg/m3	Inhalable fraction.
Talc (CAS 14807-96-6)	TWA	2 mg/m3	Inhalable fraction.

**Slovakia. OELs. Regulation No. 300/2007 concerning protection of health in work with chemical agents**

Components	Type	Value	Form
aluminium silicate (CAS 1332-58-7)	TWA	2 mg/m3	Respirable fraction.
		2 mg/m3	Respirable fraction.
		2 mg/m3	Respirable aerosol fraction
		2 mg/m3	Respirable aerosol fraction
		10 mg/m3	Aerosol
		10 mg/m3	Dust.
Poly (ethylene oxide) (CAS 25322-68-3)	TWA	10 mg/m3	Total
		1000 mg/m3	
Talc (CAS 14807-96-6)	TWA	2 mg/m3	Respirable fraction.
		2 mg/m3	Respirable fraction.
		10 mg/m3	Total

**Slovenia. OELs. Regulations concerning protection of workers against risks due to exposure to chemicals while working (Official Gazette of the Republic of Slovenia)**

Components	Type	Value	Form
2-octyl-2h-isothiazol-3-one (CAS 26530-20-1)	TWA	0,05 mg/m3	Inhalable fraction.
Mixture of: 5-chloro-2-methyl-2H-isothiazol-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1) (CAS 55965-84-9)	TWA	0,05 mg/m3	
Poly (ethylene oxide) (CAS 25322-68-3)	TWA	1000 mg/m3	Inhalable fraction.
Talc (CAS 14807-96-6)	TWA	2 mg/m3	Respirable fraction.

**Spain. Occupational Exposure Limits**

Components	Type	Value	Form
aluminium silicate (CAS 1332-58-7)	TWA	2 mg/m3	Respirable fraction.
Talc (CAS 14807-96-6)	TWA	2 mg/m3	Respirable fraction.

**Sweden. OELs. Work Environment Authority (AV), Occupational Exposure Limit Values (AFS 2015:7)**

Components	Type	Value	Form
aluminium silicate (CAS 1332-58-7)	TWA	5 mg/m3	Respirable dust.
		10 mg/m3	Inhalable dust.
Talc (CAS 14807-96-6)	TWA	2 mg/m3	Total dust.
		1 mg/m3	Respirable dust.

**Sweden. OELs. Work Environment Authority (AV), Occupational Exposure Limit Values (AFS 2015:7)**

Components	Type	Value	Form
Trimethylolpropane (CAS 77-99-6)	TWA	5 mg/m <sup>3</sup>	

**Switzerland. SUVA Grenzwerte am Arbeitsplatz**

Components	Type	Value	Form
2-octyl-2h-isothiazol-3-one (CAS 26530-20-1)	STEL	0,1 mg/m <sup>3</sup>	Inhalable dust.
aluminium silicate (CAS 1332-58-7)	TWA	0,05 mg/m <sup>3</sup>	Inhalable dust.
	TWA	3 mg/m <sup>3</sup>	Respirable dust.
Poly (ethylene oxide) (CAS 25322-68-3)	TWA	1000 mg/m <sup>3</sup>	
Talc (CAS 14807-96-6)	TWA	2 mg/m <sup>3</sup>	Respirable dust.

**UK. EH40 Workplace Exposure Limits (WELs)**

Components	Type	Value	Form
aluminium silicate (CAS 1332-58-7)	TWA	2 mg/m <sup>3</sup>	Respirable dust.
Talc (CAS 14807-96-6)	TWA	1 mg/m <sup>3</sup>	Respirable dust.

**Biological limit values** No biological exposure limits noted for the ingredient(s).

**Recommended monitoring procedures** Follow standard monitoring procedures.

**Derived no effect levels (DNELs)** Not available.

**Predicted no effect concentrations (PNECs)** Not available.

**Exposure guidelines****Slovenia. OELs. Regulations concerning protection of workers against risks due to exposure to chemicals while working (Official Gazette of the Republic of Slovenia)**

2-octyl-2h-isothiazol-3-one (CAS 26530-20-1) Can be absorbed through the skin.  
 Mixture of: 5-chloro-2-methyl-2H-isothiazol-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1) (CAS 55965-84-9) Can be absorbed through the skin.

**8.2. Exposure controls**

**Appropriate engineering controls** Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.

**Individual protection measures, such as personal protective equipment**

**General information** Personal protection equipment should be chosen according to the CEN standards and in discussion with the supplier of the personal protective equipment.

**Eye/face protection** Wear safety glasses with side shields (or goggles).

**Skin protection**

**- Hand protection** Wear appropriate chemical resistant gloves.

**- Other** Wear suitable protective clothing.

**Respiratory protection** In case of insufficient ventilation, wear suitable respiratory equipment.

**Thermal hazards** Wear appropriate thermal protective clothing, when necessary.

**Hygiene measures** Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

**Environmental exposure controls** Environmental manager must be informed of all major releases.

**SECTION 9: Physical and chemical properties****9.1. Information on basic physical and chemical properties****Appearance**

**Physical state** Liquid.

**Form** Liquid.

**Colour** Orange

**Odour** slight



<b>Odour threshold</b>	Not available.
<b>pH</b>	7 - 9
<b>Melting point/freezing point</b>	Not available.
<b>Initial boiling point and boiling range</b>	Not available.
<b>Flash point</b>	> 100,00 °C (> 212,00 °F)
<b>Evaporation rate</b>	Not available.
<b>Flammability (solid, gas)</b>	Not applicable.
<b>Upper/lower flammability or explosive limits</b>	
<b>Flammability limit - lower (%)</b>	Not available.
<b>Flammability limit - upper (%)</b>	Not available.
<b>Vapour pressure</b>	Not available.
<b>Vapour density</b>	Not available.
<b>Relative density</b>	Not available.
<b>Solubility(ies)</b>	
<b>Solubility (water)</b>	Not available.
<b>Partition coefficient (n-octanol/water)</b>	Not available.
<b>Auto-ignition temperature</b>	Not available.
<b>Decomposition temperature</b>	Not available.
<b>Viscosity</b>	Not available.
<b>Explosive properties</b>	Not explosive.
<b>Oxidising properties</b>	Not oxidising.

## 9.2. Other information

<b>Density</b>	1,35 - 1,55 g/cm <sup>3</sup>
----------------	-------------------------------

## SECTION 10: Stability and reactivity

<b>10.1. Reactivity</b>	The product is stable and non-reactive under normal conditions of use, storage and transport.
<b>10.2. Chemical stability</b>	Material is stable under normal conditions.
<b>10.3. Possibility of hazardous reactions</b>	No dangerous reaction known under conditions of normal use.
<b>10.4. Conditions to avoid</b>	Contact with incompatible materials.
<b>10.5. Incompatible materials</b>	Strong oxidising agents.
<b>10.6. Hazardous decomposition products</b>	Diarylide pigments in this product may thermally decompose in polymeric resin applications when processed at temperatures exceeding 200 C (392 F). Decomposition products may include various monoazo dyes, hydrocyanic acid, and aromatic amines including 3,3'-dichlorobenzidine (an IARC Group 2B carcinogen).

## SECTION 11: Toxicological information

<b>General information</b>	Occupational exposure to the substance or mixture may cause adverse effects.
<b>Information on likely routes of exposure</b>	
<b>Inhalation</b>	May cause allergy or asthma symptoms or breathing difficulties if inhaled. Prolonged inhalation may be harmful.
<b>Skin contact</b>	May cause an allergic skin reaction.
<b>Eye contact</b>	Direct contact with eyes may cause temporary irritation.
<b>Ingestion</b>	May cause discomfort if swallowed. However, ingestion is not likely to be a primary route of occupational exposure.
<b>Symptoms</b>	Exposure may cause temporary irritation, redness, or discomfort.
<b>11.1. Information on toxicological effects</b>	
<b>Acute toxicity</b>	Not known.

Components	Species	Test results
2-octyl-2h-isothiazol-3-one (CAS 26530-20-1)		
<b>Acute</b>		
<b>Inhalation</b>		
<i>Mist</i>		
LC50	Rat	0,58 mg/l, 4 hours OECD Test Guideline 403
<b>Oral</b>		
LD50	Rat	318 mg/kg OECD Test Guideline 403

\* Estimates for product may be based on additional component data not shown.

<b>Skin corrosion/irritation</b>	Due to partial or complete lack of data the classification is not possible.
<b>Serious eye damage/eye irritation</b>	Due to partial or complete lack of data the classification is not possible.
<b>Respiratory sensitisation</b>	Due to partial or complete lack of data the classification is not possible.
<b>Skin sensitisation</b>	Due to partial or complete lack of data the classification is not possible.
<b>Germ cell mutagenicity</b>	Due to partial or complete lack of data the classification is not possible.
<b>Carcinogenicity</b>	Risk of cancer cannot be excluded with prolonged exposure.
<b>Hungary. 26/2000 EüM Ordinance on protection against and preventing risk relating to exposure to carcinogens at work (as amended)</b>	
Not listed.	
<b>Reproductive toxicity</b>	Due to partial or complete lack of data the classification is not possible.
<b>Specific target organ toxicity - single exposure</b>	Due to partial or complete lack of data the classification is not possible.
<b>Specific target organ toxicity - repeated exposure</b>	Due to partial or complete lack of data the classification is not possible.
<b>Aspiration hazard</b>	Due to partial or complete lack of data the classification is not possible.
<b>Mixture versus substance information</b>	No information available.
<b>Other information</b>	May cause allergic respiratory and skin reactions.

## SECTION 12: Ecological information

**12.1. Toxicity** Based on available data, the classification criteria are not met for hazardous to the aquatic environment.

Components	Species	Test results	
2-octyl-2h-isothiazol-3-one (CAS 26530-20-1)			
<b>Aquatic</b>			
<i>Acute</i>			
Crustacea	EC50	Daphnia magna	< 0,32 mg/l, 48 hours
Fish	LC50	Salmo gairdneri (new name) Oncorhynchus mykiss)	< 0,047 mg/l, 96 hours

\* Estimates for product may be based on additional component data not shown.

### 12.2. Persistence and degradability

### 12.3. Bioaccumulative potential

**Partition coefficient n-octanol/water (log Kow)** Not available.

**Bioconcentration factor (BCF)** Not available.

**12.4. Mobility in soil** No data available.

**12.5. Results of PBT and vPvB assessment** Not a PBT or vPvB substance or mixture.

**12.6. Other adverse effects** No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

### 12.7. Additional information

#### Estonia Dangerous substances in groundwater Data

1,2-Benzisothiazol-3(2H)-one (CAS 2634-33-5)	Pesticides (total) 0,5 UG/L
	Pesticides (total) 5 UG/L

## Estonia Dangerous substances in soil Data

1,2-Benzisothiazol-3(2H)-one (CAS 2634-33-5)

Synthetic pesticides (total of active substances) 0,5 mg/kg

Synthetic pesticides (total of active substances) 20 mg/kg

Synthetic pesticides (total of active substances) 5 mg/kg

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

<b>Residual waste</b>	Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).
<b>Contaminated packaging</b>	Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal.
<b>EU waste code</b>	The Waste code should be assigned in discussion between the user, the producer and the waste disposal company.
<b>Disposal methods/information</b>	Collect and reclaim or dispose in sealed containers at licensed waste disposal site.
<b>Special precautions</b>	Dispose in accordance with all applicable regulations.

## SECTION 14: Transport information

### ADR

14.1. - 14.6.: Not regulated as dangerous goods.

### RID

14.1. - 14.6.: Not regulated as dangerous goods.

### ADN

14.1. - 14.6.: Not regulated as dangerous goods.

### IATA

14.1. - 14.6.: Not regulated as dangerous goods.

### IMDG

14.1. - 14.6.: Not regulated as dangerous goods.

**14.7. Transport in bulk according to Annex II of Marpol and the IBC Code** Not established.

## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### EU regulations

**Regulation (EC) No. 1005/2009 on substances that deplete the ozone layer, Annex I and II, as amended**

Not listed.

**Regulation (EC) No. 850/2004 On persistent organic pollutants, Annex I as amended**

Not listed.

**Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 1 as amended**

Not listed.

**Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 2 as amended**

Not listed.

**Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 3 as amended**

Not listed.

**Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex V as amended**

Not listed.

**Regulation (EC) No. 166/2006 Annex II Pollutant Release and Transfer Registry, as amended**

Not listed.

**Regulation (EC) No. 1907/2006, REACH Article 59(10) Candidate List as currently published by ECHA**

Not listed.

#### Authorisations

**Regulation (EC) No. 1907/2006, REACH Annex XIV Substances subject to authorization, as amended**

Not listed.

#### Restrictions on use

**Regulation (EC) No. 1907/2006, REACH Annex XVII Substances subject to restriction on marketing and use as amended**

Not listed.

**Directive 2004/37/EC: on the protection of workers from the risks related to exposure to carcinogens and mutagens at work, as amended.**

Not listed.

## Other EU regulations

### Directive 2012/18/EU on major accident hazards involving dangerous substances, as amended

1,2-Benzisothiazol-3(2H)-one (CAS 2634-33-5)

2-octyl-2h-isothiazol-3-one (CAS 26530-20-1)

Mixture of: 5-chloro-2-methyl-2H-isothiazol-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1) (CAS 55965-84-9)

## Other regulations

The product is classified and labelled in accordance with Regulation (EC) 1272/2008 (CLP Regulation) as amended. This Safety Data Sheet complies with the requirements of Regulation (EC) No 1907/2006, as amended. Additional information is given in the Safety Data Sheet.

## National regulations

Follow national regulation for work with chemical agents. Young people under 18 years old are not allowed to work with this product according to EU Directive 94/33/EC on the protection of young people at work, as amended.

## 15.2. Chemical safety assessment

No Chemical Safety Assessment has been carried out.

## Inventory status

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	No
Canada	Domestic Substances List (DSL)	No
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	Yes
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	No
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	No
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	No
Taiwan	Taiwan Toxic Chemicals Substances Control Act	No

\*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

## SECTION 16: Other information

### List of abbreviations

Not available.

### References

Not available.

### Information on evaluation method leading to the classification of mixture

The classification for health and environmental hazards is derived by a combination of calculation methods and test data, if available.

### Full text of any H-statements not written out in full under Sections 2 to 15

H301 Toxic if swallowed.  
H302 Harmful if swallowed.  
H310 Fatal in contact with skin.  
H311 Toxic in contact with skin.  
H314 Causes severe skin burns and eye damage.  
H315 Causes skin irritation.  
H317 May cause an allergic skin reaction.  
H318 Causes serious eye damage.  
H330 Fatal if inhaled.  
H331 Toxic if inhaled.  
H400 Very toxic to aquatic life.  
H410 Very toxic to aquatic life with long lasting effects.  
H411 Toxic to aquatic life with long lasting effects.  
H412 Harmful to aquatic life with long lasting effects.

### Revision information

None.

### Training information

Follow training instructions when handling this material.

**Disclaimer**

The information contained herein is based on data believed to be reliable and the manufacturer disclaims any liability incurred from the use or reliance upon the same. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text. This safety information is not a licence to use this material as claimed by any patents of third parties. The user alone must finally determine whether a contemplated use of this material will infringe any such patents, and for obtaining any required licenses.