

Product datasheet

Gjøco Microdisperser



Gjøco Microdisperser is a waterborne, unpigmented primer for mineral surfaces both indoors and outdoors. The product has a very low particle size combined with low viscosity, which enables very good penetration properties on porous substrates. Used on untreated concrete, lightweight concrete, plasterboard and plastered surfaces. Binds loose particles on the surface and improves adhesion for future painting.

Revised

15.01.2024

Symbols



Technical data


Type:	Impregnation based on styrene acrylate
Color:	Colorless
Specific gravity:	1.0 kg/l
Solid content:	15 volume%
Viscosity (Ford Cup):	10 - 12" F4
Application method:	Rough brush
Thinner/ cleaning agent:	Water
Recommended spreading rate:	5 - 10 m ² /liter, depending on the surface
Drying times (23 °C, 50 % R.H.):	
Dry to use:	1 hours
Interval between coats:	5 hours
Minimum application temperature:	+5 °C.

Pretreatment

Loose masonry and plaster brushes / scrapes away. Should Gjøco Microdisperser be used as impregnation before overcoating with paint it is important that the substrate is solid to get good adhesion. Surfaces attacked by molds / algae are first treated with Gjøco Algrent.

Directions for use

Gjøco Microdisperser is ready for use and should not be thinned. As a pre-treatment before painting, a layer is applied. Several layers can be applied to concrete floors as dust binders. The product should be sucked into the substrate and not form a film.

Storage	Seal the lid tightly when storing paint to prevent spillage and drying. The paint must be transported and stored upright, dry and frost-free.
Disposal of waste	Liquid oil must not be emptied into sewers or into nature, but delivered to an environmental station. Empty, clean, and dry plastic packaging without a handle can be delivered as plastic waste. 
Other Information	Stir well in the box before use and during the application.
Safety	See separate safety data sheet. Read the information on the packaging.

The information on this data sheet is based on laboratory tests and practical experience. Our products are considered semi-finished products and as the conditions under which the products are used are often beyond our control, we cannot guarantee anything other than the product's quality. The products are delivered in accordance with our general terms and conditions for sales, delivery and service, unless otherwise agreed in writing. We reserve the right to make minor product changes and to change the specified data without prior notice. This data sheet replaces previous editions.

Contact information
Gjøco AS
Ørvegen 1160, 6639 Torvikbukt
Telephone: +47 712 91 700
E-mail: office@gjoco.no

