



FDV – Management, operation, and maintenance

Gjøco Akryl Fasademaling



Gjøco Akryl Fasademaling is a matte, weather-resistant acrylic paint for outdoor use on masonry and concrete surfaces. It contains a film-protecting fungicide. It is suitable for untreated or previously painted masonry, concrete, and fiber cement. When used on concrete and cement elements, any moisture or release agents must be checked. Follow the supplier's recommendations. The product is not recommended for lime-rich plaster, cold walls, or free-standing masonry. Acrylic Facade Paint is not intended for floors.

Revised

15.08.2025

Application Instructions	Substrate:	The surface must be clean, dry, and have a minimum temperature of +5°C.
	Application Methods:	Brush, roller, or spray. Spraying should be performed by professionals.
	Thinner:	Water; thinning is usually unnecessary.
	Storage:	Store and transport upright, dry, and frost-free, out of reach of children.
	Transport:	Not classified as dangerous goods under applicable regulations.
	Indoor Environment/Emission:	The product is intended for outdoor use.
Technical and Safety Data	A technical data sheet and safety data sheet (SDS) are available for this product. Visit www.gjoco.no . VOC: EU limit for this product (category A/c): 40 g/L (2010). The product contains <30 g/L VOC.	
Maintenance	Cleaning:	For annual cleaning, Gjøco Husvask is recommended. . For cleaning before repainting, Gjøco Kraftvask is recommended. Follow the product instructions.
	Interval:	The paint film naturally degrades due to weather exposure and will vary based on local conditions. Repainting should be done as needed, typically when the film appears matte and worn. Weather-exposed walls generally require more frequent repainting than other parts of the building.

Waste Disposal

Do not pour liquid paint into drains or nature; deliver it to an approved hazardous waste facility. Clean, dry plastic packaging without handles can be disposed of as plastic waste.

**Repairs/Damage**

Repairs and damages should be addressed using the same product type. Documentation must prove the same product type was previously used if other products are applied. Repairs should match the existing treatment. For repainting or color changes, it is recommended to use the same product as before. Contact a retailer or painting company for assistance.

Surface/Material Information**Painted in color:****Color name:****NCS:****Batch number:****Work performed by:****Date:****Signature:**

The information in this data sheet is based on laboratory tests and practical experience. Our products are considered semi-finished goods, and as conditions of use are often beyond our control, we can only guarantee the product's quality. Products are delivered under our general terms for sale, delivery, and service unless otherwise agreed in writing. We reserve the right to make minor product changes and amend the specified data without prior notice. This data sheet replaces earlier versions and is automatically invalid five years after the publication date.

Contact Information

Gjøco AS
Ørvegen 1160, 6639 Torvikbukt
Phone: +47 712 91 700
Email: office@gjoco.no

