



## FDV – Management, operation, and maintenance

# Gjøco Akryl Fasademaling



Gjøco Akryl Fasademaling is a matte, weather-resistant acrylic paint for outdoor use on masonry and concrete surfaces. It contains a film-protecting fungicide. It is suitable for untreated or previously painted masonry, concrete, and fiber cement. When used on concrete and cement elements, any moisture or release agents must be checked. Follow the supplier's recommendations. The product is not recommended for lime-rich plaster, cold walls, or free-standing masonry. Acrylic Facade Paint is not intended for floors.

Revised

10.04.2026

<b>Application Instructions</b>	<b>Substrate:</b>	The surface must be clean, dry, and have a minimum temperature of +5°C.
	<b>Application Methods:</b>	Brush, roller, or spray. Spraying should be performed by professionals.
	<b>Thinner:</b>	Water; thinning is usually unnecessary.
	<b>Storage:</b>	Store and transport upright, dry, and frost-free, out of reach of children.
	<b>Transport:</b>	Not classified as dangerous goods under applicable regulations.
	<b>Indoor Environment/Emission:</b>	The product is intended for outdoor use.
<b>Technical and Safety Data</b>	A technical data sheet and safety data sheet (SDS) are available for this product. Visit <a href="http://www.gjoco.no">www.gjoco.no</a> . VOC: EU limit for this product (category A/c): 40 g/L (2010). The product contains <30 g/L VOC.	
<b>Maintenance</b>	<b>Cleaning:</b>	For annual cleaning, Gjøco Husvask is recommended. For cleaning before repainting, Gjøco Kraftvask is recommended. Follow the product instructions.
	<b>Interval:</b>	The paint film naturally degrades due to weather exposure and will vary based on local conditions. Repainting should be done as needed, typically when the film appears matte and worn. Weather-exposed walls generally require more frequent repainting than other parts of the building.

---

**Waste Disposal**

Do not pour liquid paint into drains or nature; deliver it to an approved hazardous waste facility. Clean, dry plastic packaging without handles can be disposed of as plastic waste.



---

**Repairs/Damage**

Repairs and damages should be addressed using the same product type. Documentation must prove the same product type was previously used if other products are applied. Repairs should match the existing treatment. For repainting or color changes, it is recommended to use the same product as before. Contact a retailer or painting company for assistance.

---

**Eco-labeling**

BREEAM-NOR v6.1  
– MAT02: Contains no substances listed under REACH Article 59(10) – the Candidate List and the Norwegian A20 list. See also the product safety data sheet.

---

**Surface/Material Information**

**Painted in color:**

**Color name:**

**NCS:**

**Batch number:**

**Work performed by:**

**Date:**

**Signature:**

---

The information provided in this data sheet is based on laboratory tests and practical experience. As the conditions under which the products are used are often beyond our control, we cannot guarantee anything other than the quality of the product itself. The products are supplied in accordance with our general terms and conditions of sale, delivery, and service, unless otherwise agreed in writing. We reserve the right to change the stated data without prior notice. Paint may be regarded as a semi-finished product, and the final result depends on factors such as surface preparation, temperature, application method, type of substrate, etc.

---

**Contact Information**

**Gjøco AS**  
Ørvegen 1160, 6639 Torvikbukt  
Phone: +47 712 91 700  
Email: office@gjoco.no

