

Product datasheet

Gjøco Bliss 30



Gjøco Bliss 30 is a health-friendly, solvent-free, acrylic dispersion paint for indoor use. Gjøco Bliss 30 is recommended by the Norwegian Asthma and Allergy Association. Gjøco Bliss 30 has minimal paint odor and emission during application and drying. Used for intermediate and top coats in dry rooms on panels, building boards, most types of wallpaper, plaster, concrete, fiberglass fabric, environmental strips and previously painted surfaces.

Revised 27.11.2024

Symbols








Technical data

Type:	Water-thinnable acrylic emulsion paint
Color:	White, A, B and C base, colors are mixed over Gjøcomix.
Gloss:	Satin 30
Specific gravity:	1.28 kg/l
Solid content:	Ca. 40 volum%
Application method:	Brush, roller, or spray. Spraying should be done by professionals. It is best to use a roller with an extension handle because it is easier to avoid streaks.
Thinner/ cleaning agent:	Water
Recommended spreading rate:	8 - 10 m ² /litre, depending on the substrate.
Guide data high-pressure sprayer:	
Nozzle size:	0.53 mm (0.021")
Fan angle:	65°-80°
Paint pressure:	Min. 15 MPa (Min. 150 kg/cm ²)
Drying times (23 °C, 50 % R.H.):	
Dry to use:	1 hours. Drying time deviates at changes in temperature, air humidity, air circulation and film thickness.
Interval between coats:	2 hours
Minimum application temperature:	+10 °C. Best results are achieved when applied at room temperature.
Cured:	4 weeks

Pretreatment

The surface must be clean and dry. Clean painted surfaces with Gjøco Interiørvask, then rinse well with water. MDF, hard surfaces, old semi-gloss or

	gloss paint must be sanded down and all dust removed. Prime all surfaces with one coat of Gjøco Sperregrunn (block primer). Make sure new and old discoloured/yellowing panelling are primed with minimum two coats of Gjøco Sperregrunn.
Directions for use	Apply two to three coats as required. Apply Gjøco Bliss 30 thickly and smoothly. Use high quality painting tools to achieve a nice finish.
Color	Use the same batch number on the same coat and the same surface, to avoid gloss and color differences. Alternatively, different batch numbers can be mixed before use. Buckets where the color is mixed on different mixing machines and/or at different times can result in shade differences. Be aware of this if more paint is needed for the same project afterwards.
Storage	Seal the lid tightly when storing paint to prevent spillage and drying. The paint must be transported and stored upright, dry and frost-free.
Ecolabelling	<p>Gjøco Bliss 30 is approved by Ecolabel Norway and meets the requirements for the Nordic Ecolabel Svanen.</p>   <p>Preservation: All paint must be preserved so as not to rotten in the bucket. Gjøco Bliss 30 uses a combination of 1,2-Benzisothiazol-3(2H)-one (BIT) and N-(3-Aminopropyl)-N-dodecylpropane-1,3-diamine. The levels are far lower than the EU cosmetics directive 76/768/EEC</p> <p>Contents: Water (diluent), titanium dioxide (pigment), acrylic polymer (binder), calcium magnesium carbonate (filler), kaolin (filler). Contains less than 1% of the following: Acrylic polymer (dispersant), polyurethane (thickener), polysiloxane (foam suppressant). Preservation: 1,2-Benzisothiazol-3(2H)-one (BIT) as the only known allergen.</p> <p>NAAF: To protect the skin, NAAF/Gjøco recommends using gloves when painting. The paint base is recommended by NAAF, additional color is added from the color system available at the point of sale.</p>
Disposal of waste	<p>Liquid oil must not be emptied into sewers or into nature, but delivered to an environmental station. Empty, clean, and dry plastic packaging without a handle can be delivered as plastic waste.</p>   
Other information	Application temperature in air and substrate must be at least +10 °C. Painted surfaces must cure for a minimum of 4 weeks before cleaning with a mild detergent. Light marks on dark surfaces can be removed with a microfibre cloth and clean water. Stir well before use
Safety	See separate safety data sheet. Read the information on the packaging. EU limit value for this product (cat. A/a): 30 g/l (2010). This product contains: <1 g/l VOC.

The information on this data sheet is based on laboratory tests and practical experience. Our products are considered semi-finished products and as the conditions under which the products are used are often beyond our control, we cannot guarantee anything other than the product's quality. The products are delivered in accordance with our general terms and conditions for sales, delivery and service, unless otherwise agreed in writing. We reserve the right to make minor product changes and to change the specified data without prior notice. This data sheet replaces previous editions.

Contact information

Gjøco AS

Ørvegen 1160, 6639 Torvikbukt

Telephone: +47 712 91 700

E-mail: office@gjoco.no

