

FDV – Management, Operation and Maintenance

Gjøco Fashion 80



Gjøco Fashion 80 is a water-thinnable, low-odor oil-based paint for indoor use. It has excellent application properties and provides a durable and elegant finish. It is used for intermediate and topcoats on paneling, MDF, doors, windows, frames, moldings, and interior fittings.

Revised

07.01.2025

Usage Instructions

Surface Preparation:

Ensure the surface is clean and dry, with a minimum temperature of +10°C

Application Method:

Brush, roller, or spray. Spraying should be performed by professionals.

Thinner:

Water; thinning is usually not necessary.

Storage:

Store and transport upright, dry, frost-free, and out of reach of children.

Transport:

Not classified as hazardous goods under applicable regulations.

Indoor Environment/Emissions

The product emits low emissions.

Technical and Safety Data

A technical data sheet and safety data sheet (SDS) are available at www.gjoco.no. VOC Content: EU limit for the product (cat. A/a): 130 g/l (2010). This product contains <75 g/l VOC.

Maintenance

Cleaning:

For cleaning prior to repainting, it is recommended to use an alkaline cleaning agent such as Gjøco Interiør or Husvask. Follow the product instructions. Newly painted surfaces should not be washed until after 4 weeks. Use microfiber cloths with clean water or mild soapy water. The cleaning water temperature should not exceed +40°C, and the pH should not exceed 9. The use of abrasive cleaning agents may damage the surface. Cleaning should be carried out in a way that avoids streaks and performed with discretion. The paint film wears faster under heavy cleaning loads.

Intervals: The paint film is affected by mechanical impact and wears according to the level of stress. Maintenance intervals will therefore vary based on need.

Waste Management

The product is classified as hazardous waste and must be delivered to an approved hazardous waste facility. It must not be poured into the environment, sewage systems, or water. Empty, clean, and dry plastic packaging without a handle can be disposed of as plastic waste. Refer to additional regulations on hazardous waste for more details.



Repairs/Damage

Repairs and damages should be addressed using the same type of product. If other products are used, it must be documented that they are of the same type previously applied. Repairs should be carried out in a way that does not deviate from previous treatments. For repainting or color changes, it is recommended to use the same product as previously applied. Contact your dealer or a painting company for assistance.

Environmental Labeling

The product is approved by Nordic Swan Ecolabel (Svanen) and meets its requirements.



The product has been tested according to BREEAM-NOR requirements and satisfies BREEAM-NOR HEA 02.

Gjøco Alle Rom contains no substances on the A20 list.

Treated Surface/Type of Substrate:

Painted in Color:

Color Name:

NCS:

Batch Number:

Painting Performed By:

Date:

Signature:

The information in this data sheet is based on laboratory tests and practical experience. As our products are semi-finished goods, and usage conditions often fall outside our control, we only guarantee the product's quality. Products are delivered under our general terms of sale, delivery, and service unless otherwise agreed in writing. Minor product changes and data updates may occur without notice. This data sheet replaces previous editions and is automatically invalidated five years after its issue date.

Contact Information

Gjøco AS
Ørvegen 1160, 6639 Torvikbukt
Phone: +47 712 91 700
Email: office@gjoco.no

