

GJØCO INTERIØR 10



Gjøco Interiør 10 is a low-odour water-thinnable pure acrylic paint for indoor use. Covers well and provides a durable surface that is easy to keep clean. Ideal as wall paint. To be used as intermediate and top coats on boards, over paintable wallpaper, woven fabric, plaster, concrete and putty.

Physical data

Type:	Acrylic emulsion
Colour:	White + A, B, C, tinted by using Gjøcomix
Gloss:	Silky 6-10
Specific gravity (kg/ltr):	Ca. 1,3
Solids by volume %:	Ca. 40

Recommandation for use

Application methods:	Roller, brush or airless spray
Thinner / cleaning agent:	Water and a suitable cleaning agent
Recommended spreading rate:	8-10 m ² depending on surface
Guiding data for airless spray	
Nozzle tip:	0.53 mm (0.021")
Spray angle degrees:	65° - 80°
Pressure at nozzle:	Min. 15 MPa (Min. 150 kg/cm ²)
Drying times (23 °C, 50% R.H.):	
Dust dry:	1 hour. Drying time deviates at changes in temperature, air humidity, air circulation and film thickness.
Interval between coats (v/23°C), minimum:	4 hours. Drying time deviates at changes in temperature, air humidity, air circulation and film thickness.
Minimum applying temp. °C:	+ 5°C. Best results are obtained by application at room temperature.
Cured:	4 weeks

Preparations

The substrate must be clean, sound and dry: Clean with Gjøco Husvask or Gjøco Interiørvask. Rinse with water. Previously oil-painted surfaces, MDF boards and hard, smooth surfaces are sanded down with sandpaper and primed with Gjøco Sperregrunn. New panel and old discolored panel are applied with a minimum of 2 coats of Gjøco Sperregrunn for insulation and blocking of knots.

Directions for use

The product is ready for use and does not need thinner. Textile wall covering to be primed with a suitable primer. Use 2 coats as topcoat with Gjøco Interiør 10. 3 coats are recommended on absorbent, porous surfaces to avoid discolouring. Apply rich and even with suitable paint tools. To get satisfactory flow and a smooth surface, avoid returning to semi-dry paint.

Colours

Use the same batch number on the same coat and the same surface, to avoid color and gloss differences. Cans where the colour is mixed in on different mixing machines and/or at different times can produce shade differences. Be aware of this if more paint is needed for the same project afterwards.

Storage

In storage and in transport keep the container frost free and upright.

Disposal of waste

Liquid paint must not be emptied into drains or watercourses. It must be delivered to an approved local environmental protection station.



Eco Labelling



Gjøco Interiør 10 is approved by Ecolabelling Norway and meets the requirements for the Nordic Ecolabel

Safety

For more detailed information, read the safety datasheet. Read the information on the packaging. VOC: EU limit value for this product (category A/a): 30 g/l (2010). The product contains <1 g/l VOC.

Other Information

Storage and transport: Upright, dry and frost-free. Application temperature in air and substrate must be at least + 10°C. Stir well before use. Different batch numbers are mixed before use. Replace the lid well after use to prevent spillage and drying. Liquid paint must not be emptied into drains or watercourses, but delivered to the environmental protection station. For more detailed information, scan the QR code or look at www.gjoco.no.

GJØCO INTERIØR 10



The information in this document is given to the best of Gjøco's knowledge, based on laboratory testing and practical experience. Gjøco's products are considered as semi-finished goods and as such, products are often used under conditions beyond Gjøco's control. Gjøco cannot guarantee anything but the quality of the product itself. Minor product variations may be implemented in order to comply with local requirements. Gjøco reserves the right to change the given data without further notice.

Edited by Gjøco AS
