

Gjøco Interiørbeis is a water-thinned oil stain for indoor use on untreated pine and spruce wood. Can be used on wooden panels, mouldings, frames, furniture, doors, floors and ceilings. Gives the wood a transparent and matt appearance. Can be mixed in many different stain colors. Is not suitable for hard wooden substrates with low penetration of stains such as e.g. oak and parquet.

Physical data

Type:	Alkyd oil
Colour:	Transparent / base C, tinted by using Gjøcomix
Gloss:	Matt
Specific gravity (kg/ltr):	Ca. 1
Solids by volume %:	Ca.20

Recommendation for use

Application methods:	Brush (wide/oval intended for priming/staining that can carry a lot of stain)
Thinner / cleaning agent:	Water and a suitable cleaning agent
Recommended spreading rate:	14-17 m ² depending on surface
Drying times (23 °C, 50% R.H.):	
Dust dry:	2 hours. Drying time deviates at changes in temperature, air humidity, air circulation and film thickness.
Interval between coats (v/23°C), minimum:	Minimum 24 hours. Drying time deviates at changes in temperature, air humidity, air circulation and film thickness.
Minimum applying temp. °C:	+ 10°C. Best results are obtained by application at room temperature.
Cured:	4 weeks

Preparations

The substrate must be clean, dry and firm. Clean with Gjøco Gulv og Panelrens. Allow the wood to dry, and remove fiber rise carefully with sandpaper. Sanding dust is carefully removed with a broom or microfiber cloth. Previously treated substrates must be sanded down to bare wood. If you are unsure whether the wood has been treated, you should do a test coat. In any case, a test coat should be taken on old panel/wood.

How to apply

Gjøco Interiørbeis must be applied in thin layers. If a transparent and less opaque surface is desired, wipe off excess stain with a sponge or lint-free cloth. If more than one coat is applied, the color will be more opaque and the drying time will be significantly longer between coats. Do a test coat to check the color and result. When used on surfaces with strongly use, as floors, tables and furniture, it's recommend to apply varnish or oil as a top coat. Allow a minimum of 24 hours to pass before repainting.

Treat 1–2 panel boards at a time along the entire length to avoid joints/shields. To get a smooth and natural surface, excess stain can be wiped off immediately in the lengthwise direction with a lint-free cloth or sponge. It is recommended to clean the brush in water occasionally for larger works, to prevent the stain from drying and graining in the brush.

Storage

Close the lid tightly when storing the stain to prevent spillage and drying. The stain must be transported, stored and stored upright, dry and frost-free.

Eco Labelling



Gjøco Interiørbeis is approved by Ecolabelling Norway and meets the requirements for the Nordic Ecolabel

Disposal of waste

Do not empty into drains or watercourses. It must be delivered to an approved local environmental protection station.



Safety

For more detailed information, please refer to the safety datasheet. Read the information on the packaging. VOC: EU limit value for this product (category A/e): 130 g/l (2010). The product contains <70 g/l VOC.

Other information

Always use the same batch number on the same surface, or cans with different batch numbers can be mixed before use, to prevent gloss and color differences. Stir well before use. Use good quality brushes designed for water-thinnable products. To avoid cracking along the panel, as a result of changes in humidity, it is recommended that the panel boards are treated before installation. If necessary, the panel can be treated in late winter when the humidity normally is low. For more detailed information, scan the QR code or look at www.gjoco.no.

The information in this document is given to the best of Gjøco's knowledge, based on laboratory testing and practical experience. Gjøco's products are considered as semi-finished goods and as such, products are often used under conditions beyond Gjøco's control. Gjøco cannot guarantee anything but the quality of the product itself. Minor product variations may be implemented in order to comply with local requirements. Gjøco reserves the right to change the given data without further notice.

Edited by Gjøco AS
