
Gjøco Oljegrunning is a primer for outdoor use, for wood protection. The primer is based on penetrating alkyds and oils. Contains film preservative that prevents the growth of black fungus and algae. Gjøco Oljegrunning is ideal for priming outdoors wooden panel from spruce and pine, both new wood and wood exposed to the weather over time. It can also be used on impregnated wood.

Physical data

Type:	Primer based on alkyd and linseed oil
Colours:	Transparent and white
Specific gravity (kg/ltr):	Ca. 0,9
Solids by volume %:	Ca. 42

Recommendation for use

Application methods:	Brush. Do not spray.
Thinner / cleaning agent:	White spirit
Recommended spreading rate:	4-8 m ² depending on surface
Drying times (23 °C, 50% R.H.):	
Dust dry:	2 hours. Drying times are generally related to air circulation, temperature, film thickness and number of coats, and will be affected correspondingly.
Interval between coats (v/23°C), minimum:	24 hours. Drying times are generally related to air circulation, temperature, film thickness and number of coats, and will be affected correspondingly.
Minimum application temperature:	Can be used below +5°C, but the substrate must be dry and frost-free. Low temperatures will significantly extend the drying time.

Preparations

The surface must be clean and dry. New wood panel that has been left untreated for more than four weeks must be wire-brushed before treating with Gjøco Oljegrunning. Degrease vacuum-impregnated windows prior to priming. Smooth and hard surfaces such as planed wood panels should be steel brushed before priming. Scrape any loose paint from painted wood. Steel brush weathered surfaces until you reach fresh wood. Remove grease and other contaminants with Gjøco Husvask.

Directions for use

The product is ready for use and does not need thinner. New and untreated wood panels should be treated with Gjøco Oljegrunning as soon as possible after assembly. Apply one coat to bare wood. Use a wide brush. Two coats may be necessary on weather-worn and strongly absorbent surfaces. Remember to apply three to four coats to the ends and joins of the wood panels to ensure a proper

seal. Further treatment should be carried out as soon as possible and within one month. Do not allow a film to form when using Gjøco Oljegrunning – wipe off any excess with a lint-free cloth.

Storage

Seal the lid tightly when storing paint to prevent spillage and drying. Containers must be kept tightly closed. The paint must be transported and stored upright and frost-free.

Disposal of waste

The product must not be emptied into sewers or into nature, but delivered to an approved reception for hazardous waste.



Other information

Stir well before use. We recommend transparent oil primer under transparent stain, as pigmented oil primer may make colours look different. Take a test before starting.

Safety

A Material Safety Data Sheet for the product has been issued. Please observe the environmental and precautionary notices displayed on the container.

The information in this data is based on laboratory testing and practical experience. However, as the product is often used under conditions beyond our control, we cannot guarantee anything but the quality of the product itself. The products will be delivered with reference to our GENERAL CONDITIONS FOR SALE, DELIVERING AND SERVICE, if not other written appointments. We reserve the right to change the given data without notice.

Edited by Gjøco AS
