



FDV - Management, Operation and Maintenance

Gjøco Poxydekk Epoksymaling



Gjøco Poxydekk Epoksymaling is a low-odor, water-thinnable 2-component epoxy paint for indoor use. The paint forms a water-resistant and durable film that is resistant to most chemicals and solvents. Its resistance to acids is somewhat limited. The paint can be tinted to the desired color. Gjøco Poxydekk Epoksymaling can be used on masonry, concrete, and mineral surfaces in laundry rooms, utility rooms, basements and staircases, warehouses, gas stations, and walls in livestock areas. Not suitable for substrates that move, such as wood or metal. For floors subject to heavy wear, Poxydekk Ekstremer or GjøcoPoxy SL is recommended.

Revised

14.04.2026

Application Instructions

Substrate:

The substrate must be solid, clean, dry, free of dust and grease, and have a temperature of at least +12 °C for both substrate and air, and at least 3 °C above the current dew point.

Application method:

Roller or brush.

Thinner:

Water.

Storage:

The packaging must be kept tightly closed and stored in a dry place at a stable temperature. The product must be transported and stored upright, dry, and frost-free.

Indoor environment / emissions:

The product has low emissions.

Product Data Sheet and Safety Data Sheet

A product data sheet and safety data sheet (SDS) have been prepared for the product. See www.gjoco.no.

Maintenance

Cleaning:

For cleaning the substrate, Gjøco Gulv og Panelrens, Gjøco Kraftvask, or another suitable cleaning agent is recommended. Follow the instructions on the packaging. See the product data sheet for additional information.

Interval:

The epoxy film is affected by mechanical stress and wears depending on the level of use. Maintenance intervals will therefore vary according to need.

Waste Management

Liquid epoxy must not be poured into drains or released into the environment, but should be taken to a recycling or waste collection station. Cured epoxy can be disposed of at waste collection stations as residual waste, but it is recommended to contact the local facility for specific guidance, as regulations may vary locally. Clean and dry packaging can be sorted as plastic.



Repairs / Damage

Repairs and damage should be remedied using the same type of product. If other products are used, it must be documented that they are of the same type as previously applied. When repairing damage, the work should be carried out so that it does not differ from previous treatments. For repainting or color changes, it is recommended to use the same product as before. Contact the supplier or painting company.

Eco-labeling

BREEAM-NOR v6.1
– MAT02: Contains no substances listed under REACH Article 59(10) – the Candidate List and the Norwegian A20 list. See also the product safety data sheet.

Treated Surface / Type of Substrate:

.....

Painted in Color:

Color Name:

.....

NCS:

.....

Batch Number:

.....

Painting Work Performed By:

.....

Date:

.....

Signature:

.....

The information provided in this data sheet is based on laboratory tests and practical experience. As the conditions under which the products are used are often beyond our control, we cannot guarantee anything other than the quality of the product itself. The products are supplied in accordance with our general terms and conditions of sale, delivery, and service, unless otherwise agreed in writing. We reserve the right to change the stated data without prior notice. Paint may be regarded as a semi-finished product, and the final result depends on factors such as surface preparation, temperature, application method, type of substrate, etc.

Contact Information

Gjøco AS, Galterud
Sagmoen 100, NO-2223 Galterud, Norway
Phone: +47 712 91 700
Email: office@gjoco.no

