

FDV - Management, Operation and Maintenance **Gjøco Poxydekk Epoksymaling**



Gjøco Poxydekk Epoksymaling is a low-odor, water-thinnable 2-component epoxy paint for indoor use. The paint forms a water-resistant and durable film that is resistant to most chemicals and solvents. Its resistance to acids is somewhat limited. The paint can be tinted to the desired color. Gjøco Poxydekk Epoksymaling can be used on masonry, concrete, and mineral surfaces in laundry rooms, utility rooms, basements and staircases, warehouses, gas stations, and walls in livestock areas. Not suitable for substrates that move, such as wood or metal. For floors subject to heavy wear, Poxydekk Ekstreme or GjøcoPoxy SL is recommended.

Revised	14.10.2025	
Application Instructions	Substrate:	The substrate must be solid, clean, dry, free of dust and grease, and have a temperature of at least +12 °C for both substrate and air, and at least 3 °C above the current dew point.
	Application method:	Roller or brush.
	Thinner:	Water.
	Storage:	The packaging must be kept tightly closed and stored in a dry place at a stable temperature. The product must be transported and stored upright, dry, and frost-free.
	Indoor environment / emissions:	The product has low emissions.
Product Data Sheet and Safety Data Sheet	A product data sheet and safety data sheet (SDS) have been prepared for the product. See www.gjoco.no.	
Maintenance	Cleaning:	For cleaning the substrate, Gjøco Gulv og Panelrens, Gjøco Kraftvask, or another suitable cleaning agent is recommended. Follow the instructions on the packaging. See the product data sheet for additional information.
	Interval:	The epoxy film is affected by mechanical stress and wears depending on the level of use. Maintenance intervals will therefore vary according to need.

Waste Management

Liquid epoxy must not be poured into drains or released into the environment, but should be taken to a recycling or waste collection station. Cured epoxy can be disposed of at waste collection stations as residual waste, but it is recommended to contact the local facility for specific guidance, as regulations may vary locally. Clean and dry packaging can be sorted as plastic.







Repairs / Damage

Repairs and damage should be remedied using the same type of product. If other products are used, it must be documented that they are of the same type as previously applied. When repairing damage, the work should be carried out so that it does not differ from previous treatments. For repainting or color changes, it is recommended to use the same product as before. Contact the supplier or painting company.

Treated Surface / Type of Substrate:	
Painted in Color:	Color Name:
	NCS:
Batch Number:	
Painting Work Performed By:	
Date:	
Signature:	

The information in this data sheet is based on laboratory tests and practical experience. Our products are considered semi-finished, and since the conditions under which they are used are often beyond our control, we can only guarantee the quality of the product itself. The products are supplied in accordance with our general terms of sale, delivery, and service, unless otherwise agreed in writing. We reserve the right to make minor product modifications and to change the specified data without prior notice. This data sheet replaces previous editions and is automatically void five years after the date of issue.

Contact Information

Gjøco AS, Galterud Sagmoen 100, NO-2223 Galterud, Norway

Phone: +47 712 91 700 Email: office@gjoco.no

