

Product datasheet

Gjøco Silkematt Rom



Gjøco Silkematt Rom is a low-odor, water-thinnable pure acrylic paint for indoor use. Covers well and provides a durable surface that is easy to keep clean. Ideal as a wall paint. Used on building boards, plaster, concrete, fiberglass batt, environmental batt, previously painted surfaces, etc.

Revised 26.11.2024

Symbols





Technical data

Type:	Water-thinnable acrylic dispersion paint
Color:	White, A, B and C base, colors are mixed over Gjøcomix.
Gloss:	Eggshell 7-10
Specific gravity:	1.3 kg/l
Solid content:	Ca. 40 volum%
Application method:	Brush, roller, or spray. Spraying should be done by professionals. It is best to use a roller with an extension handle because it is easier to avoid streaks.
Thinner/ cleaning agent:	Water
Recommended spreading rate:	8 - 12 m ² /litre, depending on the substrate.
Guide data high-pressure sprayer:	
Nozzle size:	0,53 mm (0,021")
Fan angle:	65°-80°
Paint pressure:	Min. 15 MPa (Min. 150 kg/cm ²)
Drying times (23 °C, 50 % R.H.):	
Dry to use:	1 hours
Interval between coats:	2 hours. Full adhesion is achieved after 4 weeks of curing. Varies with changes in temperature, humidity, ventilation and film thickness.
Minimum application temperature:	+5 °C. Best results are achieved when applied at room temperature.

Pretreatment

The substrate must be clean and dry. Clean with Gjøco Interiørvask or Gjøco Gulv- og panelrens. Follow the instructions on the packaging.

	Previously oil-painted surfaces, MDF boards and hard, smooth substrates should be sanded with sandpaper and primed with Gjøco Sperregrunn. It is recommended to apply a test coat if you are unsure whether the substrate can be painted over. New panels and old discolored panels should be applied with a minimum of 2 coats of Gjøco Sperregrunn for insulation and knot blocking.
Directions for use	Gjøco Silkematt Rom is ready to use and should not normally be thinned. Apply evenly and generously. On absorbent and porous surfaces, 3 coats are recommended to avoid streaks. It is advisable to use a roller with an extension handle because it is easier to avoid streaks. To get an even result, it is recommended to roll entire lengths in the same direction on the entire wall.
Color	Use the same batch number on the same coat and the same surface, to avoid gloss and color differences. Alternatively, different batch numbers can be mixed before use. Buckets where the color is mixed on different mixing machines and/or at different times can result in shade differences. Be aware of this if more paint is needed for the same project afterwards.
Storage	Seal the lid tightly when storing paint to prevent spillage and drying. The paint must be transported and stored upright, dry and frost-free.
Ecolabelling	<p>Gjøco Silkematt Rom is approved by Ecolabel Norway and meets the requirements for the Nordic Ecolabel.</p>  <p>The product has been tested in accordance with the test requirements set by BREEAM-NOR. The product meets BREEAM-NOR HEA 02. Gjøco Silkematt Rom does not contain any substances on the A20 list.</p>
Disposal of waste	<p>Liquid oil must not be emptied into sewers or into nature, but delivered to an environmental station. Empty, clean, and dry plastic packaging without a handle can be delivered as plastic waste.</p> 
Other information	<p>Painted surfaces must cure for a minimum of 4 weeks before cleaning with a mild detergent. Light marks on dark surfaces can be removed with a microfiber cloth and clean water. Stir well before use.</p> <p>Package sizes: 0.68 L; 2.7 L and 9 L</p>
Safety	<p>See separate safety data sheet. Read the information on the packaging.</p> <p>EU limit value for this product (cat. A/a): 30 g/l (2010). This product contains: <1 g/l VOC.</p>

The information on this data sheet is based on laboratory tests and practical experience. Our products are considered semi-finished products and as the conditions under which the products are used are often beyond our control, we cannot guarantee anything other than the product's quality. The products are delivered in accordance with our general terms and conditions for sales, delivery and service, unless otherwise agreed in writing. We reserve the right to make minor product changes and to change the specified data without prior notice. This data sheet replaces previous editions.

Contact information

Gjøco AS
Ørvegen 1160, 6639 Torvikbukta
Telephone: +47 712 91 700
E-mail: office@gjoco.no

