

Product data sheet

Gjøco Gulvolje



Gjøco Gulvolje is a transparent, semi-gloss, solvent-based floor oil. It is primarily intended for use as a dust binder on concrete and on primed iron, among other surfaces, but can also be used on wood.

Revised

28.10.2025

Symbols



Technical data

Type:	Alkyd oil.
Color:	Light golden.
Gloss:	Semi-gloss, depending on the substrate and number of coats.
Specific gravity:	Approx. 0.9 kg/l
Solid content:	Approx. 38% by volume.
Application method:	Brush, roller or spray.
Thinner/ cleaning agent:	White Spirit.
Recommended spreading rate:	Approx. 6 m ² /liter.
Drying time (23 °C, 50 % R.H.):	
Dust dry:	6 hours.
Minimum recoating interval:	8 hours.
Minimum application temperature:	+10 °C. Best results are achieved when applied at room temperature.

Pretreatment

Previously treated floors should first be washed with Gjøco Husvask or Gjøco Gulv- og panelrens to remove grease, soap residues, and wax. Porous substrates such as concrete and masonry should be scraped and brushed clean of loose particles.

Directions for use

For use as a dust binder on concrete floors, the oil should be thinned with 20–30% Gjøco White Spirit. Apply wet on wet, meaning the next coat is applied before the previous one has fully absorbed. Note: Do not apply more than what the surface can absorb, usually 3–4 coats depending on the substrate's absorbency. Excess oil should be wiped off with a lint-free cloth.

Storage	Tightly close the lid when storing the paint to prevent spills and drying out. The paint should be transported and stored upright, in a dry and frost-free environment.
Disposal of waste	Liquid oil must not be poured into drains or released into the environment, but should be delivered to an approved facility for hazardous waste. Empty, clean, and dry packaging should also be taken to an approved collection point. See also the regulations for hazardous waste. 
Other information	The product must be stored in accordance with national regulations. The packaging must be kept tightly closed and stored dry at a constant temperature. Packaging sizes: 3 and 10 liters.
Safety	See separate safety data sheet. Read the information on the packaging. EU limit value for this product (cat. A/f): 700 g/l (2010). This product contains: <600 g/l VOC.
The information in this data sheet is based on laboratory tests and practical experience. Since the conditions under which the products are used are often beyond our control, we can only guarantee the quality of the product itself. The products are supplied in accordance with our general terms of sale, delivery, and service, unless otherwise agreed in writing. We reserve the right to change the stated data without prior notice. Paint should be considered a semi-finished product, and the result depends on surface preparation, temperature, application, type of substrate, etc. This data sheet supersedes all previous editions.	
Contact information	Gjøco AS Ørvegen 1160, 6639 Torvikbukt Telephone: +47 712 91 700 E-mail: office@gjoco.no 