

Product datasheet

Gjøco Gulvolje



Gjøco Floor Oil is a transparent, semi-gloss solvent-based floor oil. It is primarily intended for use as a dust binder on concrete, primed iron, etc., but can also be used on wood.

Revised

28.11.2024

Symbols



Technical data


Type:	Alkyd oil
Color:	Light golden
Gloss:	Semi-gloss, depending on the substrate and number of coats.
Specific gravity:	Ca. 0,9 kg/l
Solid content:	Ca. 38 volum%
Application method:	Brush, roller or spray.
Thinner/ cleaning agent:	White Spirit
Recommended spreading rate:	Approx. 6 m ² /litre
Drying times (23 °C, 50 % R.H.):	
Dry to use:	6 hours
Interval between coats:	8 hours
Minimum application temperature:	+10 °C. Best resultat oppnås ved påføring i romtemperatur.

Pretreatment

Previously treated floors are first washed with Gjøco Husvask or Gjøco Gulvrens to remove grease, soap residue and wax. Porous surfaces such as concrete and masonry are scraped and brushed clean of loose particles.

Directions for use

For use as a dust binder on concrete floors, thin the oil with 20-30% Gjøco White Spirit.
Apply wet on wet, i.e. apply the next coat before the previous one has fully absorbed. NB! Do not apply more than what penetrates, usually 3-4 coats depending on the absorbency of the substrate. Wipe off excess oil with a lint-free cloth.

Storage	Seal the lid tightly when storing paint to prevent spillage and drying. The paint must be transported and stored upright, dry and frost-free.
Disposal of waste	Liquid oil should not be emptied into sewers or into nature, but delivered to an approved hazardous waste collection point. Empty, clean and dry packaging should be delivered to an approved hazardous waste collection point. See also regulations on hazardous waste. 
Other information	The product must be stored in accordance with national regulations. The packaging must be kept tightly closed and stored dry at a constant temperature. Packaging sizes: 3 and 10 liters
Safety	See separate safety data sheet. Read the information on the packaging. EU limit value for this product (cat. A/f): 700 g/l (2010). This product contains: <600 g/l VOC.

The information on this data sheet is based on laboratory tests and practical experience. Our products are considered semi-finished products and as the conditions under which the products are used are often beyond our control, we cannot guarantee anything other than the product's quality. The products are delivered in accordance with our general terms and conditions for sales, delivery and service, unless otherwise agreed in writing. We reserve the right to make minor product changes and to change the specified data without prior notice. This data sheet replaces previous editions.

Contact information
Gjøco AS
 Ørvegen 1160, 6639 Torvikbukt
 Telephone: +47 712 91 700
 E-mail: office@gjoco.no

