

Product datasheet

Gjøco Heftgrunn



Gjøco Heftgrunn is a matt, solvent-based interior primer based on alkyd oil. Gjøco Heftgrunn is ideal as a primer and as a top coat on ceilings. Used on substrates such as wood, building boards, MDF, wallpaper, fabric, drywall and concrete, previously painted surfaces, etc. Not suitable for ceramic tiles.

Revised 28.11.2024

Symbols




Technical data

Type:	Alkyd oil-based paint
Color:	White, can be broken into light colors over Gjøcomix.
Gloss:	Matte
Specific gravity:	Ca. 1.5 kg/l
Solid content:	Ca. 48 volum%
Application method:	Brush, roller and high-pressure sprayer. Spraying should be done by professionals.
Thinner/ cleaning agent:	White Spirit
Recommended spreading rate:	Ca. 8-12 m ² /litre, depending on the substrate.
Recommended film thickness, wet:	80-100 micrometer
Recommended film thickness, dry:	35-40 micrometer
Guide data high-pressure sprayer:	
Nozzle:	0,021"; 0,53 mm
Fan angle:	65-80°
Paint pressure:	150 kg/cm ²
Drying times (23 °C, 50 % R.H.):	
Dry to use:	4 hours
Interval between coats:	24 hours. Full adhesion is achieved after 4 weeks of thorough curing. Varies with changes in temperature, humidity, ventilation and film thickness.
Minimum application temperature:	+10 °C

Pretreatment

The substrate must be clean and dry and free of grease, wax and oils. Previously painted surfaces should be washed with Gjøco Husvask. Previously painted

	surfaces, building boards, MDF and factory-painted surfaces should be mattified with fine sandpaper. Building boards may have been surface-treated with wax or similar, check adhesion. When using on tiles and plastic, check adhesion by applying a test coat.
Directions for use	Gjøco Heftgrunn is ready to use and normally does not need to be thinned.
Storage	Seal the lid tightly when storing paint to prevent spillage and drying. The paint must be transported and stored upright, dry and frost-free.
Disposal of waste	Liquid paint should not be emptied into sewers or into nature, but delivered to an approved hazardous waste collection point. Empty, clean and dry packaging should be delivered to an approved hazardous waste collection point. See also regulations on hazardous waste. 
Other information	Any oil floatation must be stirred in well before use. Application temperature in air and substrate must be at least +10 °C. Painted surfaces must cure for a minimum of 4 weeks before cleaning with a mild detergent. Stir well before use. Different production numbers must be mixed before use. Packaging sizes: 0.68; 2.7 and 9 liters
Safety	See separate safety data sheet. Read the information on the packaging. EU limit value for this product (cat. A/d): 300 g/l (2010). This product contains: <300 g/l VOC.

The information on this data sheet is based on laboratory tests and practical experience. Our products are considered semi-finished products and as the conditions under which the products are used are often beyond our control, we cannot guarantee anything other than the product's quality. The products are delivered in accordance with our general terms and conditions for sales, delivery and service, unless otherwise agreed in writing. We reserve the right to make minor product changes and to change the specified data without prior notice. This data sheet replaces previous editions.

Contact information **Gjøco AS**
 Ørvegen 1160, 6639 Torvikbukta
 Telephone: +47 712 91 700
 E-mail: office@gjoco.no

