



## FDV – Management, operation, and maintenance

# Gjøco Herregård Exclusive Oljebeis



Gjøco Herregård Exclusive Oljebeis is a thixotropic alkyd oil-based stain with added film protection against mildew. It penetrates well into the wood, providing effective impregnation while forming a weather-resistant film. Herregård Exclusive Oljebeis is used on new or previously stained wood surfaces. It can also be used on pressure-treated materials. No primer is required.

Revised

28.02.2025

### Application Instructions

**Substrate:**

The surface must be dry and free of frost, with a minimum temperature of -5 °C.

**Application Methods:**

Brush, roller, or spray. Spraying should be carried out by professionals.

**Thinner:**

White Spirit, thinning is normally not necessary.

**Storage:**

Store and transport upright, dry, and frost-free, out of reach of children.

**Transport:**

Not classified as dangerous goods under applicable regulations.

**Indoor Environment/Emission:**

The product is intended for outdoor use.

### Technical and Safety Data

A technical data sheet and safety data sheet (SDS / HSE data sheet) have been prepared for this product. See [www.gjoco.no](http://www.gjoco.no). VOC: EU limit value for this product (cat. A/e): 400 g/l (2010). The product contains <400 g/l VOC.

### Maintenance

**Cleaning:**

For annual cleaning, Gjøco Husvask is recommended. If the surfaces are contaminated with mildew, they can also be treated with Gjøco Sopp og Algefjerner. For cleaning before repainting, Gjøco Kraftvask is recommended. Follow the instructions on the product label. Newly painted wood should not be washed for 3-4 weeks.

**Interval:**

The paint film naturally breaks down due to weather exposure, and this will vary depending on local conditions. Repainting should be done as needed, particularly when the film becomes dull and worn. Weather-exposed walls typically require more frequent repainting than the rest of the building.

**Waste Disposal**

Liquid paint must not be poured into drains or released into nature, but should be delivered to an approved hazardous waste facility. Empty and dry containers should be delivered to an approved recycling facility. See also regulations for hazardous waste.



**Repairs/Damage**

Repairs and damage should be touched up using the same type of product. Documentation must show that the same type of product was previously used if other products are applied. Repairs should be carried out in such a way that they do not deviate from previous treatments. When repainting or changing color, it is recommended to use the same product that was used before. Contact your dealer or paint supplier for further advice.

**Surface/Material Information**

Painted in color:

Color name:

NCS:

Batch number:

Work performed by:

Date:

Signature:

The information in this data sheet is based on laboratory tests and practical experience. Our products are considered semi-finished goods, and as conditions of use are often beyond our control, we can only guarantee the product's quality. Products are delivered under our general terms for sale, delivery, and service unless otherwise agreed in writing. We reserve the right to make minor product changes and amend the specified data without prior notice. This data sheet replaces earlier versions and is automatically invalid five years after the publication date.

**Contact Information**

**Gjøco AS**  
 Ørvegen 1160, 6639 Torvikbuk  
 Phone: +47 712 91 700  
 Email: office@gjoco.no

