



FDV – Management, operation, and maintenance

Gjøco Herregård Exclusive Tjærebeis



Gjøco Herregård Exclusive Tjærebeis is a high-quality stain for outdoor use. It gives a transparent and beautiful glow to the wood. Herregård Exclusive Tjærebeis consists of weather-resistant alkyds and tar. It contains UV stabilizers and transparent pigments that enhance resistance to sunlight and weathering. The tar stain has a high solids content that provides a water-repellent and durable surface, helping to prevent surface cracking. It contains film-preserving agents against mold. It is used on new untreated, pressure-treated, or previously stained outdoor wood, such as cabins, log buildings, sheds, and houses.

Revised 11.03.2025

Application Instructions	Substrate:	The surface must be clean, dry, and have a minimum temperature of -5°C.
	Application Methods:	Brush, roller, or spray. Spraying should be performed by professionals.
	Thinner:	White Spirit, thinning is usually not necessary.
	Storage:	Store and transport upright, dry, and frost-free, out of reach of children.
	Transport:	Not classified as dangerous goods under applicable regulations.
	Indoor Environment/Emission:	The product is intended for outdoor use.
Technical and Safety Data	A technical data sheet and safety data sheet (SDS / MSDS) have been prepared for the product. See www.gjoco.no . VOC: EU limit for the product (cat. A/e): 400 g/l (2010). The product contains <400 g/l VOC.	
Maintenance	Cleaning:	For annual cleaning, Gjøco Husvask is recommended. If surfaces are contaminated with mold, they can also be treated with Gjøco Sopp- og grønskefjerner. For cleaning before repainting, Gjøco Kraftvask is recommended. Follow the instructions on the product. Newly painted wood should not be washed before 3-4 weeks.
	Interval:	The paint film naturally breaks down due to weather exposure and will vary depending on local conditions. Repainting should therefore be done as needed, when the film becomes matte and worn. The weather-facing wall(s) are more exposed to the elements and typically

require more frequent repainting than the rest of the building.

Waste Disposal

Liquid paint should not be disposed of in sewage drains or in nature, but should be delivered to an approved facility for hazardous waste. Empty and dry packaging should be delivered to an approved facility. See the regulations for hazardous waste for further details.



Repairs/Damage

Repairs and damages should be addressed using the same product type. Documentation must prove the same product type was previously used if other products are applied. Repairs should match the existing treatment. For repainting or color changes, it is recommended to use the same product as before. Contact a retailer or painting company for assistance.

Surface/Material Information

Painted in color:

Color name:

NCS:

Batch number:

Work performed by:

Date:

Signature:

The information in this data sheet is based on laboratory tests and practical experience. Our products are considered semi-finished goods, and as conditions of use are often beyond our control, we can only guarantee the product's quality. Products are delivered under our general terms for sale, delivery, and service unless otherwise agreed in writing. We reserve the right to make minor product changes and amend the specified data without prior notice. This data sheet replaces earlier versions and is automatically invalid five years after the publication date.

Contact Information

Gjøco AS
Ørvegen 1160, 6639 Torvikbukt
Phone: +47 712 91 700
Email: office@gjoco.no

