



FDV – Management, operation, and maintenance

Herregård Terrassebeis Oljebasert



Herregård Terrassebeis Oljebasert is a solvent-based stain designed for outdoor use on decks and garden furniture made of treated wood. It contains pigments and UV stabilizers that protect the wood from degradation caused by sunlight, as well as film-preserving agents to prevent mold growth. Herregård Terrassebeis Oljebasert is durable, penetrates well, and helps prevent cracking of the substrate. It can also be used on larch wood but should be applied in only one coat.

Revised

15.08.2025

Application Instructions

Substrate:

The surface must be clean, dry, and have a minimum temperature of 0°C.

Application Methods:

Pad, brush, or roller. Spraying is not permitted.

Thinner:

White Spirit, thinning is usually not necessary.

Storage:

Store and transport upright, dry, and frost-free, out of reach of children.

Transport:

Not classified as dangerous goods under applicable regulations.

Indoor Environment/Emission:

The product is intended for outdoor use.

Technical and Safety Data

A technical data sheet and safety data sheet (SDS / MSDS) have been prepared for the product. See www.gjoco.no. VOC: EU limit for the product (cat. A/e): 700 g/l (2010). The product contains <600 g/l VOC.

Maintenance

Cleaning:

For annual cleaning, Gjøco Husvask is recommended. Clean with Gjøco Terrasserens before re-staining. Follow the instructions on the product. Newly stained wood should not be washed until 3-4 weeks after application.

Interval:

The paint film naturally breaks down due to weather exposure and will vary depending on local conditions. Repainting should be done as needed, when the film appears dull and worn.

Waste Disposal

Liquid stain must not be emptied into sewers or into nature, but must be delivered to an approved hazardous waste collection point. Empty, clean and dry packaging is delivered to approved reception.



Repairs/Damage

Repairs and damages should be addressed using the same product type. Documentation must prove the same product type was previously used if other products are applied. Repairs should match the existing treatment. For repainting or color changes, it is recommended to use the same product as before. Contact a retailer or painting company for assistance.

Surface/Material Information

Painted in color:

Color name:

NCS:

Batch number:

Work performed by:

Date:

Signature:

The information in this data sheet is based on laboratory tests and practical experience. Our products are considered semi-finished goods, and as conditions of use are often beyond our control, we can only guarantee the product's quality. Products are delivered under our general terms for sale, delivery, and service unless otherwise agreed in writing. We reserve the right to make minor product changes and amend the specified data without prior notice. This data sheet replaces earlier versions and is automatically invalid five years after the publication date.

Contact Information

Gjøco AS
Ørvegen 1160, 6639 Torvikbukt
Phone: +47 712 91 700
Email: office@gjoco.no

