

# HERREGÅRD TERRASSEBEIS

## SOLVENTBASED



Herregård Terrassebeis oil-based is a solvent-based stain intended for outdoor use on terraces and garden furniture made of impregnated wood. It contains pigments and UV stabilizers that protect the wood against sunlight degradation and a film preservative against black fungus. Herregård Terrassebeis oil-based is durable, penetrates well and prevents cracking of the substrate. Can also be used on larch wood, but only 1 coat.

### Physical data

Type:	Solventbased wood protection based on alkyd
Color:	C and oxide yellow transparent base, to be tinted to desired colour
Specific gravity (kg/l):	Ca 0,9
VOC:	EU limit value for the product (cat. A/f): 700 g/l (2010). The product contains <600 g/l VOC

### Recommendation for use

Application methods:	Pad, brush and roll. Not to be sprayed.
Thinner/ cleaning agent:	White Spirit, not to be thinned.
Recommended spreading rate:	Planed wood approx. 6-10 m <sup>2</sup> /liter
Drying times (23 °C, 50% R.H.):	Drying time deviates at changes in temperature, air humidity, wind, absorption and film thickness. Avoid painting if high risk of rain or dew formation within the drying interval.
Dust dry:	4 hours
When to use:	12 hours
Minimum application temp. °C:	+ 8°C. Temperature in air and substrate must be above + 8°C.

### Preparations new wood

The substrate must be clean and dry. New, impregnated wood must dry before treatment; it can take anything from a few weeks to 1-2 months. Rinse and brush off any impregnation residues. Wash the terrace with Gjoco Terrasserens Gel. Follow the instructions for use on the packaging. Allow to dry well before further treatment. The terrace should be treated as soon as possible after it is clean and dry, to prevent the surface from wearing out as a result of exposure to the weather.

When cleaning terraces made of larch and tropical woods etc., follow the guidelines from the supplier for the use of cleaning agents.

### Preparations old and treated wood

Wash the terrace with Gjoco Terrasserens Gel. Repeat the treatment for very dirty surfaces and to remove all previous treatment. Follow the instructions for use on the packaging. Allow to dry well before further treatment. Previous treatment that cannot be removed by using Terrasserens is sanded

# HERREGÅRD TERRASSEBEIS

## SOLVENTBASED



away. Grey, weather-worn surfaces must be wire-brushed or sanded down to fresh wood before further treatment. Loose wood fibers and gray wood can prevent penetration and cause flaking.

### How to apply

The stain is applied with a pad, roller or brush. Apply the stain to the entire length of the table and treat 1-2 tables in the same time. Strongly absorbent substrates can need two coats. The terrace stain must penetrate the wood without forming a film. Excess stain is wiped off. Film formation can lead to flaking.

The stain will draw differently in the wood around twigs and softer parts of the wood, which can result in different play of colours. Treatment of knots, and hard and dense types of wood such as larch, can result in reduced durability due to lack of penetration into the wood.

Avoid application in strong sunlight, damp weather and at low temperatures. Check that no rain has been reported in the first 24 hours after application. Low temperature and high humidity significantly extend the drying time. Pay particular attention in spring and autumn with low night temperatures. Have a tarp ready in case of rain.

### Colors

The terrace stain is transparent, and the color will therefore vary in relation to the substrate. Remember that the color becomes stronger and darker the more layers are applied. Feel free to try a coat to check that the color is as desired. It is not recommended to use the stain without the addition of pitch color/pigment. Use of the same batch number on the same coat and the same surface, to avoid shade differences in the colour. The range where the color is mixed in on different mixing machines and/or at different times can produce shade differences. Be aware of this if you need to buy more stain for the same project afterwards.

### Storage

Seal the lid tightly when storing paint to prevent spillage and drying. The stain must be transported and stored upright and frost free.

### Waste disposal

Liquid stain must not be emptied into drain or in nature, but delivered to an approved local environmental protection station for hazardous waste.



# HERREGÅRD TERRASSEBEIS

## SOLVENTBASED



---

### Additional information

Different batch numbers must be mixed prior to use to avoid gloss and color differences. Always use the same batch number on the same surface and the same layer. The color of Herregård Terrassebeis Vanntynnet changes during drying. It is more milky white in the pan, but becomes clear when dried. Any oil floating up should be stirred in well before use. Must not be used on timber that has been exposed to frost.

Packaging sizes: 2.7 and 9 liters.

---

### Safety data

A Material Safety Data Sheet for the product has been issued. Read the information on the packaging.

---

The information in this data is based on laboratory testing and practical experience. However, as the product is often used under conditions beyond our control, we cannot guarantee anything but the quality of the product itself. The products will be delivered with reference to our GENERAL CONDITIONS FOR SALE, DELIVERING AND SERVICE, if not other written appointments. We reserve the right to change the given data without notice. This data replaces previous editions and will be cancelled automatically 5 years after the publication date.

Edited by Gjøco AS

---