

Product Data Sheet

Herregård Terrassebeis Vanntynnet



Herregård Terrassebeis is a water-thinned oil stain intended for outdoor use on terraces and garden furniture made of impregnated wood. It contains pigments that protect the wood against sunlight degradation and a film preservative against black fungus. Herregård Terrassebeis penetrates well and protects against cracking of the substrate.

Revised 18.03.2026

Symbols




Technical data

Type:	Water-based/alkyd oil-based
Color:	Base A, C and oxide yellow, broken down to desired color
Viscosity:	45-50" F4
Specific gravity:	1.02 kg/l
Solid content:	Approx. 22 volum%
Application method:	Pad, brush or roller. Do not spray.
Thinner / cleaning agent:	Water. The product should not normally be diluted.
Recommended spreading rate:	Approx. 6-10 m ² /liter per coat, planed wood.
Drying time (23 °C, 50 % R.H.):	Depends on temperature, humidity, wind and film thickness.
Dust dry:	12 hours
Interval between coats, minimum:	2 hours
Minimum application temperature:	+10 °C. Low temperatures significantly extend drying time.

Pretreatment

The substrate must be clean and dry. New, impregnated wood must dry before treatment; this can take anywhere from a few weeks to 1-2 months. Rinse and brush off any impregnation residue. Wash the terrace with Gjøco Terrasserens Gel. Follow the instructions on the packaging. Let dry thoroughly before further treatment. The terrace should be treated as soon as possible after it is clean and dry, to avoid the surface from wearing away due to weather exposure.

For treatment of old/previously treated wood, wash the terrace with Gjøco Terrasserens Gel. Repeat the treatment for very dirty surfaces and to remove all previous treatment. Follow the instructions on the packaging. Let dry thoroughly before further treatment. Previous treatment that cannot be removed using Terrasserens must be sanded away. Gray, weather-worn surfaces must be wire-

	brushed or sanded down to fresh wood before further treatment. Loose wood fibers and gray wood can prevent penetration and cause flaking.
Directions for use	<p>The stain is applied with a pad, roller or brush. Apply the stain to the entire length of the board and treat 1-2 boards at a time. Highly absorbent surfaces can be applied in two coats. The decking stain should penetrate the wood without forming a film. Wipe off excess stain. Film formation can lead to peeling.</p> <p>The stain will absorb differently into the wood around knots and softer parts of the wood, which can result in different color play. Treatment of knots, and hard and dense wood types such as larch, can reduce durability due to lack of penetration into the wood.</p> <p>Avoid application in strong sunlight, humid weather and at low temperatures. Check that there is no forecast for rain in the first 24 hours after application. Low temperatures and high humidity significantly extend the drying time. Be especially careful in spring and autumn with low night temperatures. Have a tarpaulin ready in case of rain.</p>
Color	<p>The terrace stain is transparent, and the color will therefore vary depending on the substrate. Remember that the color becomes stronger and darker the more coats are applied. Feel free to apply a sample coat to check that the color is as desired. It is not recommended to use the stain without the addition of a stain/pigment. Use the same batch number on the same coat and the same surface, to avoid nuance differences in the color.</p>
Storage	Seal the lid tightly when storing paint to prevent spillage and drying. The paint must be transported and stored upright, dry and frost-free.
Eco-labeling	<p>BREEAM-NOR v6.1 – MAT02: Contains no substances listed under REACH Article 59(10) – the Candidate List and the Norwegian A20 list. See also the product safety data sheet.</p>
Disposal of waste	<p>Liquid stain should not be emptied into sewers or into nature, but delivered to an environmental waste disposal station. Empty, clean and dry plastic packaging without a handle can be delivered as plastic waste.</p> 
Other information	<p>The color of Herregård Terrassebeis Vanntynnet changes during drying. It is more milky white in the bucket, but becomes clear when dried. Any oil floats must be stirred in well before use.</p> <p>Packaging sizes: 2.7 and 9 liters.</p>
Safety	<p>See separate safety data sheet. Read the information on the packaging.</p> <p>EU limit value for this product (kat. A/e): 130 g/l (2010). This product contains: <5 g/l VOC.</p>

The information provided in this data sheet is based on laboratory tests and practical experience. As the conditions under which the products are used are often beyond our control, we cannot guarantee anything other than the quality of the product itself. The products are supplied in accordance with our general terms and conditions of sale, delivery, and service, unless otherwise agreed in writing. We reserve the right to change the stated data without prior notice. Paint may be regarded as a semi-finished product, and the final result depends on factors such as surface preparation, temperature, application method, type of substrate, etc.

Contact information

Gjøco AS
Ørvegen 1160, 6639 Torvikbukt
Telephone: +47 712 91 700
E-mail: office@gjoco.no

