



## FDV – Management, operation, and maintenance

### Gjøco Herregård Terrassebeis



Gjøco Herregård Terrassebeis is a water-based oil stain designed for outdoor use on decks and garden furniture made from treated wood. It contains pigments that protect the wood from degradation caused by sunlight and film-preserving agents to prevent mold growth. Herregård Terrassebeis penetrates well and protects against cracking of the substrate.

Revised

13.01.2025

#### Application Instructions

##### Substrate:

The surface must be clean, dry, and have a minimum temperature of +10°C.

##### Application Methods:

Pad, brush, or roller. Spraying is not permitted.

##### Thinner:

Water, thinning is normally not necessary.

##### Storage:

Store and transport upright, dry, and frost-free, out of reach of children.

##### Transport:

Not classified as dangerous goods under applicable regulations.

##### Indoor Environment/Emission:

The product is intended for outdoor use.

#### Technical and Safety Data

A technical data sheet and safety data sheet (SDS / MSDS) have been prepared for the product. See [www.gjoco.no](http://www.gjoco.no). VOC: EU limit for the product (cat. A/e): 130 g/l (2010). The product contains <5 g/l VOC.

#### Maintenance

##### Cleaning:

For annual cleaning, Gjøco Husvask is recommended. Clean with Gjøco Terrasserens before re-staining. Follow the instructions on the product. Newly stained wood should not be washed until 3-4 weeks after application.

##### Interval:

The paint film naturally breaks down due to weather exposure and will vary depending on local conditions. Repainting should be done as needed, when the film appears dull and worn. The weather-facing wall(s) are more exposed to the elements and typically require more frequent repainting than the rest of the building.

---

**Waste Disposal**

Liquid stain should not be disposed of in sewage drains or in nature, but should be delivered to an approved facility for hazardous waste. Empty, clean, and dry plastic packaging without handles can be disposed of as plastic waste.



---

**Repairs/Damage**

Repairs and damages should be addressed using the same product type. Documentation must prove the same product type was previously used if other products are applied. Repairs should match the existing treatment. For repainting or color changes, it is recommended to use the same product as before. Contact a retailer or painting company for assistance.

---

**Surface/Material Information**

**Painted in color:**

**Color name:**

**NCS:**

**Batch number:**

**Work performed by:**

**Date:**

**Signature:**

---

The information in this data sheet is based on laboratory tests and practical experience. Our products are considered semi-finished goods, and as conditions of use are often beyond our control, we can only guarantee the product's quality. Products are delivered under our general terms for sale, delivery, and service unless otherwise agreed in writing. We reserve the right to make minor product changes and amend the specified data without prior notice. This data sheet replaces earlier versions and is automatically invalid five years after the publication date.

---

**Contact Information**

**Gjøco AS**  
Ørvegen 1160, 6639 Torvikbuk  
Phone: +47 712 91 700  
Email: office@gjoco.no

