



FDV – Management, operation, and maintenance

Gjøco Herregård Treolje XO



Gjøco Herregård Treolje XO is a high-quality impregnating wood oil with a film-preserving agent to prevent mold growth. It helps prevent greying and cracking of pressure-treated wood. Herregård Treolje XO is used on outdoor terraces, privacy screens, garden furniture, and other pressure-treated wood materials. For light-colored wood, it is recommended to use pigmented oil for better protection.

Revised

06.03.2025

Application Instructions

Substrate:

The surface must be clean, dry, and have a minimum temperature of +5°C.

Application Methods:

Brush or roller.

Thinner:

White Spirit, thinning is usually not necessary.

Storage:

Store and transport upright, dry, and frost-free, out of reach of children.

Transport:

Not classified as dangerous goods under applicable regulations.

Indoor Environment/Emission:

The product is intended for outdoor use.

Technical and Safety Data

A technical data sheet and safety data sheet (SDS / MSDS) have been prepared for the product. See www.gjoco.no. VOC: EU limit for the product (cat. A/e): 700 g/l (2010). The product contains <600 g/l VOC.

Maintenance

Cleaning:

For annual cleaning, Gjøco Kraftvask is recommended. Use Gjøco Terrasserens for heavily soiled surfaces before re-treatment. Follow the instructions on the product. Newly painted wood should not be washed until after 3-4 weeks.

Interval:

The paint film naturally breaks down due to weather exposure and will vary based on local conditions. Repainting should therefore be done as needed, when the film becomes dull and worn.

Waste Disposal

Liquid stain should not be disposed of in sewage drains or in nature, but should be delivered to an approved facility for hazardous waste. Empty, clean, and dry plastic packaging without handles can be disposed of as plastic waste.



Repairs/Damage

Repairs and damages should be addressed with the same type of product. It must be documented that the same type as previously used is applied if other products are used. When repairing damages, it should be done in a way that does not deviate from the previous treatments. When re-painting or changing colors, it is recommended to use the same product as before. Contact the supplier or painting company

Surface/Material Information

Painted in color:

Color name:

NCS:

Batch number:

Work performed by:

Date:

Signature:

The information in this data sheet is based on laboratory tests and practical experience. Our products are considered semi-finished goods, and as conditions of use are often beyond our control, we can only guarantee the product's quality. Products are delivered under our general terms for sale, delivery, and service unless otherwise agreed in writing. We reserve the right to make minor product changes and amend the specified data without prior notice. This data sheet replaces earlier versions and is automatically invalid five years after the publication date.

Contact Information

Gjøco AS
Ørvegen 1160, 6639 Torvikbukt, Norway
Phone: +47 712 91 700
Email: office@gjoco.no

