



FDV – Management, Operation, and Maintenance

Gjøco Hurtigsparkel



Gjøco Hurtigsparkel is a fast-drying, extra fine hand filler for indoor use. It is used for smoothing and filling frames, doors, cabinets, and similar surfaces made of wood and steel. Gjøco Hurtigsparkel dries quickly and forms a hard, low-absorbent surface that is well suited for painting over.

Revised: 11.06.2025

Instructions for Use

Substrate:	The surface must be clean and dry, with a minimum temperature of +5°C.
Application method:	Steel trowel
Thinner:	Do not thin.
Storage:	Store and transport upright, in a dry and frost-free environment, and out of reach of children.
Transport:	Not classified as hazardous goods according to current regulations.
Indoor environment / Emissions:	The product emits low levels of emissions.

Technical Data and Safety Information

A technical data sheet and a safety data sheet (HMS / SDS) have been prepared for the product. See www.gjoco.no. VOC: EU limit value for this product (cat. A/d): 130 g/l (2010). The product contains <40 g/l VOC.

Maintenance

Cleaning:	Not applicable. The product is not used on its own.
Interval:	Not applicable. The product is not used on its own.

Waste Disposal

Filler must not be emptied into drains or released into nature but must be delivered to an approved hazardous waste disposal facility. Empty, clean, and dry plastic packaging without a handle can be disposed of as plastic waste.

**Repairs / Damage**

Not applicable. The product is not used on its own.

Treated Surface / Type of Substrate:

Batch Number:

Painting Work Performed By:

Date:

Signature:

The information in this data sheet is based on laboratory tests and practical experience. Our products are considered semi-finished goods, and since the conditions under which the products are used are often beyond our control, we can only guarantee the quality of the product itself. The products are supplied in accordance with our general terms and conditions for sales, delivery, and service, unless otherwise agreed in writing. We reserve the right to make minor product changes and to amend the specified data without prior notice. This data sheet replaces previous versions and is automatically void five years after the publication date.

Contact Information

Gjøco AS
Ørvegen 1160, 6639 Torvikbukt, Norway
Phone: +47 712 91 700
Email: office@gjoco.no

