

Product Data Sheet

Gjøco Quick Filler



Gjøco Hurtigsparkel is a fast-drying, extra-fine hand filler for indoor use. It is designed for leveling and filling on frames, doors, cabinets, and similar surfaces made of wood and steel. Gjøco Hurtigsparkel dries quickly, forming a hard, minimally absorbent surface that is well-suited for painting.

Revised 02.12.2024

Symbols



Technical Data

Type:	Latex polymer with white dolomite as filler
Color:	White
Density:	Approx. 1.8 kg/l
Solids Content	Approx. 53% by volume
pH:	Approx. 9
Grain Size:	Max 0,03 mm
Application Method:	Steel trowel
Thinner/Cleaning Agent:	Water. Normally not to be diluted..
Consumption:	Broad filling: 0.5 liters/m ² at 0.5 mm layer thickness
Touch Dry:	Approx. 0.5 hours
Repainting Interval, Minimum:	Approx. 4 hours
Layer Thickness:	Max. 2 mm
Minimum Application Temperature:	+5°C
Shelf Life:	1 year in unopened packaging

Surface Preparation

The substrate must be clean, dry, grease-free, and free of loose particles. Glossy surfaces should be cleaned with Gjøco Husvask or Gjøco Interiørvask. Absorbent surfaces and untreated wood should be primed before filling.

Application

Apply using a steel trowel. Sanding should be done with fine sandpaper (grit 100-120). Remove dust before proceeding. Filled surfaces must be pre-pasted before wallpapering.

Storage

Seal the lid tightly when storing the filler to prevent spillage and drying out. Transport and store upright, in dry and frost-free conditions.

Waste Disposal

Do not dispose of filler or washing water in sewers or nature. Deliver to an approved hazardous waste facility. Empty, clean, and dry plastic packaging can be disposed of as plastic waste.



Additional Information

Store in a dry, frost-free location, away from direct sunlight. Unopened packaging can be stored for 12 months. It may remain usable after 12 months; check consistency and smell. Packaging size: 400 ml.

Safety

Refer to the dedicated safety data sheet. Read the information on the packaging. Use eye protection when sanding large areas.

The information on this data sheet is based on laboratory tests and practical experience. Our products are considered semi-finished goods, and since conditions of use are often beyond our control, we can only guarantee the product's quality. Products are supplied according to our general terms of sale, delivery, and service unless otherwise agreed in writing. We reserve the right to make minor product changes and update the stated data without prior notice. This data sheet supersedes earlier versions.

Contact Information

Gjøco AS
Ørvegen 1160, 6639 Torvikbukt
Phone: +47 712 91 700
Email: office@gjoco.no

