



## FDV – Management, operation, and maintenance

### Gjøco Imprex Tretjære



Gjøco Imprex Tretjære is a light, water-repellent tar blend. It is used as an impregnation, especially for old wood. It can also be used on pressure-treated timber and for impregnating ropes and cordage.

Revised

15.08.2025

<b>Application Instructions</b>	<b>Substrate:</b>	The surface must be clean and dry
	<b>Application Methods:</b>	Brush. Can be heated up to around 30°C for the right consistency before application.
	<b>Thinner:</b>	White Spirit or Turpentine.
	<b>Storage:</b>	Store and transport upright, dry, and frost-free, out of reach of children.
	<b>Transport:</b>	Not classified as dangerous goods under applicable regulations.
	<b>Indoor Environment/Emission:</b>	The product is intended for outdoor use.
<b>Technical and Safety Data</b>	A technical data sheet and safety data sheet (SDS / MSDS) have been prepared for the product. See <a href="http://www.gjoco.no">www.gjoco.no</a> . VOC: EU limit for the product (cat. A/e): 400 g/l (2010). The product contains <250 g/l VOC.	
<b>Maintenance</b>	<b>Cleaning:</b>	For annual cleaning, Gjøco Husvask is recommended. Follow the instructions on the product. Newly painted wood should not be washed before 3-4 weeks.
	<b>Interval:</b>	The paint film naturally breaks down due to weather conditions and will vary according to local conditions. Repainting should therefore be done as needed, when the film becomes dull and worn.

**Waste Disposal**

Liquid tar must not be emptied into sewers or into nature, but must be delivered to an approved hazardous waste collection point. Empty, clean and dry packaging is delivered to approved reception.

**Repairs/Damage**

Repairs and damages should be addressed with the same type of product. It must be documented that the same type as previously used is applied if other products are used. When repairing damages, it should be done in a way that does not deviate from the previous treatments. When re-painting or changing colors, it is recommended to use the same product as before. Contact the supplier or painting company

**Surface/Material Information****Painted in color:****Color name:****NCS:****Batch number:****Work performed by:****Date:****Signature:**

The information in this data sheet is based on laboratory tests and practical experience. Our products are considered semi-finished goods, and as conditions of use are often beyond our control, we can only guarantee the product's quality. Products are delivered under our general terms for sale, delivery, and service unless otherwise agreed in writing. We reserve the right to make minor product changes and amend the specified data without prior notice. This data sheet replaces earlier versions and is automatically invalid five years after the publication date.

**Contact Information****Gjøco AS**

Ørvegen 1160, 6639 Torvikbukt

Phone: +47 712 91 700

Email: office@gjoco.no

