

Product datasheet

Gjøco Imprex Tretjære



Gjøco Imprex Wood Tar is a light and water-repellent mixed tar. Gjøco Imprex wood tar is used as an impregnation, especially for old wood. Can also be used on pressure-impregnated wood and for impregnation of ropes and cordage.

Revised 06.12.2024

Symbols



Technical data

Type:	Mixing tar
Color:	Light brown
Flash point:	Approx. 130 °C
Specific gravity:	0.98 kg/l
Solid content:	Approx. 98-100 volum%
Application method:	Broom or brush. Can be heated to approx. +30°C for a more liquid consistency before application.
Thinner / cleaning agent:	White Spirit or Turpentine.
Recommended spreading rate:	2-4 m ² /liter, per coat.
Drying time:	Tar does not dry, but will penetrate the substrate so that the surface feels dry.

Pretreatment

The substrate must be dry and free of grease, oil and loose old paint. Grease, oil and other contaminants are removed with Gjøco Kraftvask. Follow the instructions on the packaging. Rinse thoroughly with clean water.

Directions for use

Stir the tar well before use. Gjøco Imprex Wood Tar is relatively viscous and can be heated in a water bath to approx. +30 °C for better application consistency. Can be mixed with boiled or raw linseed oil and turpentine for a good impregnation.

Storage

Seal the lid tightly when storing paint to prevent spillage and drying. The paint must be transported and stored upright, dry and frost-free.

Disposal of waste

Liquid tar must not be emptied into sewers or into nature, but must be delivered to an approved hazardous waste collection point. Empty, clean and dry packaging is delivered to approved reception.

**Other information**

Tar is a natural product and the colour may therefore vary slightly. Buckets with different batch numbers must therefore be mixed. The walls should be treated every year for the first few years. South and west facing walls are usually more exposed to the weather and will need treatment more often than the others. The wood tar fades in the sun. Walls exposed to heavy rain may become whitish. This is washed and brushed away, and the wall is treated again when the wall is dry. Packaging sizes: 0.75, 3 and 10 litres

Safety

See separate safety data sheet. Read the information on the packaging.
EU limit value for this product (kat. A/e): 400 g/l (2010). This product contains:
<250 g/l VOC.

The information on this data sheet is based on laboratory tests and practical experience. Our products are considered semi-finished products and as the conditions under which the products are used are often beyond our control, we cannot guarantee anything other than the product's quality. The products are delivered in accordance with our general terms and conditions for sales, delivery and service, unless otherwise agreed in writing. We reserve the right to make minor product changes and to change the specified data without prior notice. This data sheet replaces previous editions.

Contact information

Gjøco AS
Ørvegen 1160, 6639 Torvikbukta
Telephone: +47 712 91 700
E-mail: office@gjoco.no

