

# Product datasheet

## Gjøco Interiør 25 Våtrom



Gjøco Interiør 25 Våtrom is a low-odor, water-based pure acrylic paint for interior use. It provides good coverage and a durable surface that is easy to keep clean. Gjøco Interiør 25 Våtrom is ideal as a topcoat in wet rooms (such as bathrooms and kitchens) as well as living rooms, hallways, and bedrooms. Suitable for use on building panels, MDF, plaster, concrete, fiberglass wallpaper, environmentally friendly wallpaper, previously painted surfaces, etc. Should not be used directly in shower zones.

Revised


08.10.2025

Symbols



### Technical data

|                                     |  |
|-------------------------------------|--|
| Type:                               | Pure acrylic paint   |
| Color:                              | White, A, B and C base, is broken over Gjøcomix.   |
| Gloss:                              | Semi-gloss   |
| Specific gravity:                   | Ca. 1.3 kg/l   |
| Application method:                 | Brush or roller. Spraying should be done by professionals.   |
| Thinner/ cleaning agent:            | Water  |
| Recommended film thickness, wet:    | 120 micrometer   |
| Recommended film thickness, dry:    | 50 micrometer  |
| Recommended spreading rate:         | 8-12 m <sup>2</sup> /litre, depending on the substrate.  |
| Recommended data for airless spray: |  |
| Nozzle tip:                         | 0.43–0.53 mm (0.017–0.021")  |
| Spray angle degrees:                | 50°-80°  |
| Pressure at nozzle:                 | Follow the pump manufacturer's recommendations.  |
|                                     | The choice of nozzle, fan angle, and pressure must be adjusted to the specific spray equipment and substrate.                                      |
| Drying times (23 °C, 50 % R.H.):    |  |
| Dry to use:                         | 1 hours  |
| Interval between coats:             | 4 hours. Full adhesion is achieved after 4 weeks of thorough curing. Varies with changes in temperature, humidity, ventilation and film thickness. |
| Minimum application temperature:    | +5 °C. Best results are achieved when applied at room temperature.   |

|                           |   |
|---------------------------|---|
| <b>Pretreatment</b>       | The substrate must be clean and dry. Clean with Gjøco Husvask. Previously oil-painted surfaces, MDF boards and hard, smooth substrates should be mattified with sandpaper and primed with Gjøco Sperregrunn. Brickwork, concrete, previously limed and heavily contaminated substrates should be scraped, brushed and treated with Gjøco AquaStop C.                      |
| <b>Directions for use</b> | Gjøco Interiør 25 Våtrom is ready to use and should not normally be thinned. Stir the paint well before use.  |
| <b>Color</b>              | Use the same batch number on the same coat and the same surface, to avoid gloss and color differences. Alternatively, different batch numbers can be mixed before use. Buckets where the color is mixed on different mixing machines and/or at different times can result in shade differences. Be aware of this if more paint is needed for the same project afterwards. |
| <b>Storage</b>            | Seal the lid tightly when storing paint to prevent spillage and drying. The paint must be transported and stored upright, dry and frost-free.   |
| <b>Disposal of waste</b>  | Liquid paint must not be emptied into sewers or into nature, but delivered to an environmental station. Empty, clean, and dry plastic packaging without a handle can be delivered as plastic waste.<br>   |
| <b>Other information</b>  | Stir well. Different production numbers are mixed before use for the last coat to avoid gloss and color differences. The paint must not be exposed to frost. Gjøco Interiør 25 contains small amounts of biocides to prevent fouling by black mold and algae.<br>Packaging sizes: 0.68; 2.7 and 9 liters  |
| <b>Safety</b>             | See separate safety data sheet. Read the information on the packaging.<br>EU limit value for this product (cat. A/a): 30 g/l (2010). This product contains: <30 g/l VOC.  |

The information on this data sheet is based on laboratory tests and practical experience. Our products are considered semi-finished products and as the conditions under which the products are used are often beyond our control, we cannot guarantee anything other than the product's quality. The products are delivered in accordance with our general terms and conditions for sales, delivery and service, unless otherwise agreed in writing. We reserve the right to make minor product changes and to change the specified data without prior notice. This data sheet replaces previous editions.

**Contact information**  
**Gjøco AS**  
 Ørvegen 1160, 6639 Torvikbukt  
 Telephone: +47 712 91 700  
 E-mail: office@gjoco.no

