

## Product datasheet

# Gjøco Interiør 25 Våtrom



Gjøco Interiør 25 Wetroom is a low-odor, water-thinnable pure acrylic paint for indoor use. Covers well and provides a durable surface that is easy to keep clean. Gjøco Interiør 25 Wetroom is ideal as a top coat in wet rooms (bathroom and kitchen) as well as in living rooms, hallways and bedrooms. Used on building boards, MDF, plaster, concrete, fiberglass fabric, environmental stretch, previously painted surfaces, etc. Should not be used directly in the shower area.

Revised 28.11.2024

Symbols




### Technical data

Type:	Pure acrylic paint
Color:	White, A, B and C base, is broken over Gjøcomix.
Gloss:	Semi-gloss
Specific gravity:	Ca. 1.3 kg/l
Application method:	Brush or roller. Spraying should be done by professionals.
Thinner/ cleaning agent:	Water
Recommended film thickness, wet:	120 micrometer
Recommended film thickness, dry:	50 micrometer
Recommended spreading rate:	8-12 m <sup>2</sup> /litre, depending on the substrate.
Guide data high-pressure sprayer:	
Nozzle:	0.53 mm (0.021")
Fan angle:	65-80°
Paint pressure:	Min. 15 MPa (150 kg/cm <sup>2</sup> )
Drying times (23 °C, 50 % R.H.):	
Dry to use:	1 hours
Interval between coats:	4 hours. Full adhesion is achieved after 4 weeks of thorough curing. Varies with changes in temperature, humidity, ventilation and film thickness.
Minimum application temperature:	+5 °C. Best results are achieved when applied at room temperature.

### Pretreatment

The substrate must be clean and dry. Clean with Gjøco Husvask. Previously oil-painted surfaces, MDF boards and hard, smooth substrates should be mattified with sandpaper and primed with Gjøco Sperregrunn.

	Brickwork, concrete, previously limed and heavily contaminated substrates should be scraped, brushed and treated with Gjøco AquaStop C.
<b>Directions for use</b>	Gjøco Interiør 25 Wetroom is ready to use and should not normally be thinned. Stir the paint well before use.
<b>Color</b>	Use the same batch number on the same coat and the same surface, to avoid gloss and color differences. Alternatively, different batch numbers can be mixed before use. Buckets where the color is mixed on different mixing machines and/or at different times can result in shade differences. Be aware of this if more paint is needed for the same project afterwards.
<b>Storage</b>	Seal the lid tightly when storing paint to prevent spillage and drying. The paint must be transported and stored upright, dry and frost-free.
<b>Disposal of waste</b>	Liquid paint must not be emptied into sewers or into nature, but delivered to an environmental station. Empty, clean, and dry plastic packaging without a handle can be delivered as plastic waste.
	
<b>Other information</b>	Stir well. Different production numbers are mixed before use for the last coat to avoid gloss and color differences. The paint must not be exposed to frost. Gjøco Interiør 25 contains small amounts of biocides to prevent fouling by black mold and algae. Packaging sizes: 0.68; 2.7 and 9 liters
<b>Safety</b>	See separate safety data sheet. Read the information on the packaging. EU limit value for this product (cat. A/a): 30 g/l (2010). This product contains: <30 g/l VOC.

The information on this data sheet is based on laboratory tests and practical experience. Our products are considered semi-finished products and as the conditions under which the products are used are often beyond our control, we cannot guarantee anything other than the product's quality. The products are delivered in accordance with our general terms and conditions for sales, delivery and service, unless otherwise agreed in writing. We reserve the right to make minor product changes and to change the specified data without prior notice. This data sheet replaces previous editions.

**Contact information**

**Gjøco AS**  
Ørvegen 1160, 6639 Torvikbukt  
Telephone: +47 712 91 700  
E-mail: office@gjoco.no

