

Product datasheet

Gjøco Interiør 40



Gjøco Interiør 15 is a thixotropic, semi-gloss interior paint based on alkyd oil. The paint has very good covering power and provides a smooth and durable surface that is easy to keep clean. Gjøco Interiør 15 is an ideal oil paint for walls, doors and moldings. Used, among other things, on kitchens, bathrooms, doors, windows, moldings, furniture, wallpaper, fabrics, drywall and concrete, previously painted surfaces, primed iron, etc. Yellows over time.

Revised 03.12.2024

Symbols




Technical data

Type:	Alkyd oil-based paint
Color:	White, A, B and C base that is broken over Gjøcomix.
Gloss:	Semi-gloss 40
Specific gravity:	Ca. 1.2 kg/l
Flash point	43 °C
Solid content:	Ca. 45 volum%
Application method:	Brush or roller/spreader. Spraying is recommended for professionals only.
Thinner/ cleaning agent:	White Spirit
Recommended spreading rate:	Ca. 8-12 m ² /litre
Recommended film thickness, wet:	80-100 micrometer
Recommended film thickness, dry:	40-50 micrometer
Drying times (23 °C, 50 % R.H.):	
Dry to use:	4 hours
Interval between coats:	24 hours. Full adhesion is achieved after 4 weeks of thorough curing. Varies with changes in temperature, humidity, ventilation and film thickness.
Minimum application temperature:	+10 °C. Best results are achieved at room temperature.

Pretreatment

The substrate must be clean and dry, and free of grease, wax and oils. Previously painted surfaces should be cleaned with Gjøco Husvask. Follow the instructions on the packaging. Glossy and semi-gloss painted surfaces should be mattified with fine sandpaper. New wood, masonry, concrete, highly absorbent and sticky surfaces should be brushed and primed with Gjøco Heftgrunn with 10% White Spirit added.

Directions for use	Gjøco Interiør 40 is ready to use and does not normally need to be thinned. Apply with a brush or roller/dispersant.
Color	Use the same batch number on the same coat and the same surface to avoid color and gloss differences. Buckets where the color is mixed on different mixing machines and/or at different times can result in shade differences. Be aware of this if more paint is needed for the same project later.
Storage	Seal the lid tightly when storing paint to prevent spillage and drying. The paint must be transported and stored upright, dry and frost-free.
Disposal of waste	Liquid paint should not be emptied into sewers or into nature, but delivered to an approved hazardous waste collection point. Empty, clean and dry packaging should be delivered to an approved hazardous waste collection point. See also regulations on hazardous waste. 
Other information	Any oil overflow should be stirred in well before use. The contents of cans with different product numbers should be mixed before use to avoid differences in gloss and color. Packaging sizes: 0.68 and 2.7 liters
Safety	See separate safety data sheet. Read the information on the packaging. EU limit value for this product (cat. A/d): 300 g/l (2010). This product contains: <300 g/l VOC.

The information on this data sheet is based on laboratory tests and practical experience. Our products are considered semi-finished products and as the conditions under which the products are used are often beyond our control, we cannot guarantee anything other than the product's quality. The products are delivered in accordance with our general terms and conditions for sales, delivery and service, unless otherwise agreed in writing. We reserve the right to make minor product changes and to change the specified data without prior notice. This data sheet replaces previous editions.

Contact information **Gjøco AS**
 Ørvegen 1160, 6639 Torvikbukt
 Telephone: +47 712 91 700
 E-mail: office@gjoco.no

