



FDV – Management, operation, and maintenance

Gjøco Kinesisk Treolje



Gjøco Kinesisk Treolje is a high-quality impregnation oil based on heavy oil with good penetrating ability. It prevents cracking, drying out, and graying of the wood. It is used outdoors on garden furniture, terrace floors, fences, picket fences, boat materials, etc. It is suitable for hardwoods. After thorough drying, it can be overpainted with most paints.

Revised

13.01.2025

Application Instructions

Substrate:	The surface should be clean and dry, with a minimum temperature of +5 °C
Application Methods:	Brush.
Thinner:	White Spirit, thinning is normally not required.
Storage:	Store and transport upright, dry, and frost-free, out of reach of children.
Transport:	Not classified as dangerous goods under applicable regulations.
Indoor Environment/Emission:	The product is intended for outdoor use.

Technical and Safety Data

A technical data sheet and safety data sheet (SDS / MSDS) have been prepared for the product. See www.gjoco.no. VOC: EU limit for the product (cat. A/e): 700 g/l (2010). The product contains <500 g/l VOC.

Maintenance

Cleaning:	For annual cleaning, Gjøco Husvask is recommended. If surfaces are contaminated with mold, they can also be treated with Gjøco Sopp- og grønskefjerner. For cleaning before repainting, Gjøco Kraftvask is recommended. Follow the instructions on the product. Newly painted wood should not be washed until after 3-4 weeks.
Interval:	The paint film naturally breaks down due to weather exposure and will vary depending on local conditions. Repainting should be done as needed, when the film becomes dull and worn.

Waste Disposal

Liquid stain should not be emptied into sewage drains or nature, but delivered to an approved disposal site for hazardous waste. Empty and dry packaging should be delivered to an approved disposal site. Please refer to regulations for hazardous waste.



Repairs/Damage

Repairs and damages should be addressed with the same type of product. It must be documented that the same type as previously used is applied if other products are used. When repairing damages, it should be done in a way that does not deviate from the previous treatments. When re-painting or changing colors, it is recommended to use the same product as before. Contact the supplier or painting company

Surface/Material Information

Painted in color:

Color name:

NCS:

Batch number:

Work performed by:

Date:

Signature:

The information in this data sheet is based on laboratory tests and practical experience. Our products are considered semi-finished goods, and as conditions of use are often beyond our control, we can only guarantee the product's quality. Products are delivered under our general terms for sale, delivery, and service unless otherwise agreed in writing. We reserve the right to make minor product changes and amend the specified data without prior notice. This data sheet replaces earlier versions and is automatically invalid five years after the publication date.

Contact Information

Gjøco AS
Ørvegen 1160, 6639 Torvikbuk
Phone: +47 712 91 700
Email: office@gjoco.no

