



## FDV – Management, operation, and maintenance

# Gjøco Kinesisk Treolje



Gjøco Kinesisk Treolje is a high-quality impregnation oil based on heavy oil with good penetrating ability. It prevents cracking, drying out, and graying of the wood. It is used outdoors on garden furniture, terrace floors, fences, picket fences, boat materials, etc. It is suitable for hardwoods. After thorough drying, it can be overpainted with most paints.

Revised

10.04.2026

### Application Instructions

<b>Substrate:</b>	The surface should be clean and dry, with a minimum temperature of +5 °C
<b>Application Methods:</b>	Brush.
<b>Thinner:</b>	White Spirit, thinning is normally not required.
<b>Storage:</b>	Store and transport upright, dry, and frost-free, out of reach of children.
<b>Transport:</b>	Not classified as dangerous goods under applicable regulations.
<b>Indoor Environment/Emission:</b>	The product is intended for outdoor use.

### Technical and Safety Data

A technical data sheet and safety data sheet (SDS / MSDS) have been prepared for the product. See [www.gjoco.no](http://www.gjoco.no). VOC: EU limit for the product (cat. A/e): 700 g/l (2010). The product contains <500 g/l VOC.

### Maintenance

<b>Cleaning:</b>	For annual cleaning, Gjøco Husvask is recommended. For cleaning before repainting, Gjøco Kraftvask is recommended. Follow the instructions on the product. Newly painted wood should not be washed until after 3-4 weeks.
<b>Interval:</b>	The paint film naturally breaks down due to weather exposure and will vary depending on local conditions. Repainting should be done as needed, when the film becomes dull and worn.

**Waste Disposal**

Liquid stain must not be emptied into sewers or into nature, but must be delivered to an approved hazardous waste collection point. Empty, clean and dry packaging is delivered to approved reception.



**Repairs/Damage**

Repairs and damages should be addressed with the same type of product. It must be documented that the same type as previously used is applied if other products are used. When repairing damages, it should be done in a way that does not deviate from the previous treatments. When re-painting or changing colors, it is recommended to use the same product as before. Contact the supplier or painting company

**Eco-labeling**

BREEAM-NOR v6.1  
 – MAT02: Contains no substances listed under REACH Article 59(10) – the Candidate List and the Norwegian A20 list. See also the product safety data sheet.

**Surface/Material Information**

**Painted in color:**

**Color name:**

**NCS:**

**Batch number:**

**Work performed by:**

**Date:**

**Signature:**

The information provided in this data sheet is based on laboratory tests and practical experience. As the conditions under which the products are used are often beyond our control, we cannot guarantee anything other than the quality of the product itself. The products are supplied in accordance with our general terms and conditions of sale, delivery, and service, unless otherwise agreed in writing. We reserve the right to change the stated data without prior notice. Paint may be regarded as a semi-finished product, and the final result depends on factors such as surface preparation, temperature, application method, type of substrate, etc.

**Contact Information**

**Gjøco AS**  
 Ørvegen 1160, 6639 Torvikbukt  
 Phone: +47 712 91 700  
 Email: office@gjoco.no

