

Product datasheet

Gjøco Kinesisk Treolje



Gjøco Kinesisk Treolje is a high-quality impregnating oil based on heavy oil with good penetration properties. Prevents cracking, drying out and greying of the wood. Used outdoors on garden furniture, patio floors and walls, fences, wooden materials on boats, etc. Suitable for fine wood. Can be painted over with most paints after drying.

Revised 06.12.2024

Symbols



Technical data


Type:	Impregnation oil with Chinese wood oil
Color:	Clear
Flash point:	43 °C
Specific gravity:	Approx. 0.87 kg/l
Solid content:	51 volum%
Application method:	Brush
Thinner / cleaning agent:	White Spirit
Recommended spreading rate:	7-12 m ² /liter, depending on the absorbency of the wood.
Drying time (23 °C, 50 % R.H.):	
Dust dry:	8 hours
Overpainting interval, minimum:	"Wet in wet"
Minimum application temperature:	+5 °C. Low temperatures result in longer drying time.

Pretreatment

New, impregnated wood must dry before treatment; this can take anywhere from a few weeks to 1-2 months. The substrate must be clean and dry. Dirty surfaces and/or surfaces affected by black fungus should be cleaned with Gjøco Kraftvask. Weathered, grey wood must be wire brushed/sanded before treatment. Previously treated surfaces should be scraped and brushed clean of loose particles.

Directions for use

The substrate must be clean and dry before application. Stir Gjøco Kinesisk Treolje well before use. On new wood, apply 2-3 coats wet on wet. On previously treated wood, apply 1-2 coats as needed. The wood oil should penetrate the wood without forming a film. A film on the surface can lead to peeling. Wipe off excess oil with a lint-free cloth in the lengthwise direction.

Storage	Seal the lid tightly when storing paint to prevent spillage and drying. The paint must be transported and stored upright, dry and frost-free.
Disposal of waste	Liquid stain must not be emptied into sewers or into nature, but must be delivered to an approved hazardous waste collection point. Empty, clean and dry packaging is delivered to approved reception. 
Other information	Used cloths should be burned under supervision or moistened with water due to the risk of spontaneous combustion. Packaging sizes: 0.75 liters
Safety	See separate safety data sheet. Read the information on the packaging. EU limit value for this product (kat. A/f): 700 g/l (2010). This product contains: <500 g/l VOC.

The information on this data sheet is based on laboratory tests and practical experience. Our products are considered semi-finished products and as the conditions under which the products are used are often beyond our control, we cannot guarantee anything other than the product's quality. The products are delivered in accordance with our general terms and conditions for sales, delivery and service, unless otherwise agreed in writing. We reserve the right to make minor product changes and to change the specified data without prior notice. This data sheet replaces previous editions.

Contact information **Gjøco AS**
Ørvegen 1160, 6639 Torvikbukta
Telephone: +47 712 91 700
E-mail: office@gjoco.no

