

FDV – Management, Operation and Maintenance

Gjøco Klarlakk Oljebasert



Gjøco Klarlakk Oljebasert is an extra light varnish based on urethane alkyd. It provides a hard and durable surface that is easy to keep clean. Contains a light filter that reduces yellowing of the wood. Gjøco Klarlakk Oljebasert is used on spruce and pine floors, parquet, doors, windows, furniture, panels, trim, etc. It can also be used on wooden boats and similar surfaces.

Revised

27.02.2025

Usage Instructions	Surface:	The surface must be clean and dry, free of grease and floor wax, and have a minimum temperature of +5°C.
	Application Method:	Varnish brush or short-haired roller.
	Thinner:	Water; thinning is usually not necessary.
	Storage:	Store and transport upright, dry, frost-free, and out of reach of children..
	Transport:	Not classified as hazardous goods under applicable regulations.
	Indoor Environment/Emissions	The product contains White Spirit and emits vapors.
Technical and Safety Data	A technical data sheet and safety data sheet (SDS / HSE data sheet) have been prepared for the product. See www.gjoco.no . VOC: EU limit value for this product (cat. A/i): 500 g/l (2010). The product contains <500 g/l VOC.	
Maintenance	Cleaning:	For cleaning before repainting, it is recommended to use an alkaline cleaning agent such as Gjøco Interiørvask or Husvask. Follow the instructions on the product label. Newly painted surfaces should not be washed until after 4 weeks. Microfiber cloths with clean water or mild soapy water can be used. The washing water temperature should not exceed +40°C, and the pH should not exceed 9. Use of abrasive cleaning agents can damage the surface. Cleaning should be performed to avoid streaks and discoloration. Cleaning should be carried out as needed. The varnish film will wear faster with frequent cleaning.
	Intervals:	The varnish film is affected by mechanical wear and will degrade depending on the level of use. The

maintenance interval will therefore vary based on actual wear.

Waste Management

The product is classified as hazardous waste and must be delivered to an approved hazardous waste facility. The product must not be released into the environment, drains, or water sources. Empty and dry packaging should be delivered to an approved collection point. See also regulations for hazardous waste.



Repairs/Damage

Repairs and damage should be remedied using the same type of product. Documentation must confirm that the same type of product was previously used if different products are considered. Repairs should be carried out to match the original treatment. Contact your dealer or a painting professional for assistance.

Treated Surface/Type of Substrate:

Painted in Color:

Color Name:

NCS:

Batch Number:

Painting Performed By:

Date:

Signature:

The information in this data sheet is based on laboratory tests and practical experience. As our products are semi-finished goods, and usage conditions often fall outside our control, we only guarantee the product's quality. Products are delivered under our general terms of sale, delivery, and service unless otherwise agreed in writing. Minor product changes and data updates may occur without notice. This data sheet replaces previous editions and is automatically invalidated five years after its issue date.

Contact Information

Gjøco AS
Ørvegen 1160, 6639 Torvikbukt, Norway
Phone: +47 712 91 700
Email: office@gjoco.no

