

Product datasheet

Gjøco Kokt Linolje



Gjøco Kokt Linolje is a highly refined, vegetable oil with very good penetration. For both indoor and outdoor use. Can be used, for example, for boat impregnation, for thinning linseed oil products and for hand-mixed paints.

Revised

12.12.2024

Symbols



Technical data

Type:	Vegetable linseed oil
Color	Light yellow to brown
Specific gravity:	Approx. 0.93 kg/l
Flash point:	>150 °C
Application method:	Brush or roller
Thinner / cleaner:	Water, White Spirit or Turpentine
Overpainting interval, minimum:	2-3 days. Depends on temperature, humidity, wind conditions and film thickness.
Minimum application temperature:	+2 °C

Pretreatment

The substrate must be dry and free of grease, oil and loose old paint. Grease, oil and other contaminants are removed with Gjøco Kraftvask or Gjøco Husvask. Follow the instructions on the packaging. Rinse thoroughly with clean water. Let the substrate dry before further treatment.

Directions for use

Stir the oil well before use. If thinning is necessary, use water, Gjøco White Spirit or Gjøco Pure Turpentine; depending on what it is to be used for. NB! Linseed oil requires a long drying time and must only be applied at temperatures above +2 °C. Linseed oil is not water-resistant. Can be mixed with e.g. tar and turpentine for a good impregnation. Twists and cloths with boiled linseed oil must be treated as flammable waste due to the risk of spontaneous combustion; burn under supervision or moisten with water.

Storage

Screw the top back on when storing to prevent spillage and drying out. The product must be transported and stored upright, dry and frost-free.

Disposal of waste

The product should not be emptied into sewers or into nature, but delivered to an environmental waste disposal station. Empty and dry packaging can be delivered as plastic waste.



Other information

Packaging sizes: 1, 4 and 200 litres

Safety

See separate safety data sheet. Read the information on the packaging.

The information on this data sheet is based on laboratory tests and practical experience. Our products are considered semi-finished products and as the conditions under which the products are used are often beyond our control, we cannot guarantee anything other than the product's quality. The products are delivered in accordance with our general terms and conditions for sales, delivery and service, unless otherwise agreed in writing. We reserve the right to make minor product changes and to change the specified data without prior notice. This data sheet replaces previous editions.

Contact information

Gjøco AS
Ørvegen 1160, 6639 Torvikbukt
Telephone: +47 712 91 700
E-mail: office@gjoco.no

