



## FDV – Management, operation, and maintenance

### Gjøco Kokt Linolje



Gjøco kokt Linolje is a highly refined vegetable oil with excellent penetration capabilities. Suitable for both indoor and outdoor use. For example, it can be used for boat impregnation, thinning linseed oil products, and hand-mixed paints.

Revised

28.04.2025

<b>Application Instructions</b>	<b>Substrate:</b>	The surface should be clean and dry, with a minimum temperature of +2 °C
	<b>Application Methods:</b>	Brush.
	<b>Thinner:</b>	White Spirit or Turpentine.
	<b>Storage:</b>	Store and transport upright, dry, and frost-free, out of reach of children.
	<b>Transport:</b>	Not classified as dangerous goods under applicable regulations.
	<b>Indoor Environment/Emission:</b>	The product is intended for outdoor use.
<b>Technical and Safety Data</b>	A technical data sheet and safety data sheet (SDS/HMS) have been prepared for the product. See <a href="http://www.gjoco.no">www.gjoco.no</a> . VOC: EU limit for the product (category A/e): 400 g/l (2010). The product contains <400 g/l VOC.	
<b>Maintenance</b>	<b>Cleaning:</b>	For annual cleaning, Gjøco Husvask is recommended. For cleaning before repainting, Gjøco Kraftvask is recommended. Follow the product's instructions. Newly painted wood should not be washed for 3-4 weeks.
	<b>Interval:</b>	The paint film naturally degrades due to weather conditions, which will vary based on local conditions. Repainting must therefore be done as needed, when the film becomes dull and worn.

**Waste Disposal**

Liquid stain should not be poured into sewers or nature but delivered to an approved hazardous waste facility. Empty and dry packaging should be delivered to an approved waste facility. Refer to the regulations for hazardous waste for



further information.

**Repairs/Damage**

Repairs and damages should be addressed with the same type of product. Documentation must be provided to confirm it is the same type previously used if other products are employed. Repairs should be carried out to match previous treatments. For repainting or color changes, it is recommended to use the same product as before. Contact the dealer or paint company for advice.

**Surface/Material Information****Painted in color:****Color name:****NCS:****Batch number:****Work performed by:****Date:****Signature:**

The information in this data sheet is based on laboratory tests and practical experience. Our products are considered semi-finished goods, and as conditions of use are often beyond our control, we can only guarantee the product's quality. Products are delivered under our general terms for sale, delivery, and service unless otherwise agreed in writing. We reserve the right to make minor product changes and amend the specified data without prior notice. This data sheet replaces earlier versions and is automatically invalid five years after the publication date.

**Contact Information****Gjøco AS**

Ørvegen 1160, 6639 Torvikbukt

Phone: +47 712 91 700

Email: office@gjoco.no

