

# Product datasheet

## Gjøco Kraftvask



Gjøco Kraftvask is an alkaline cleaning product for outdoor surfaces. It efficiently removes stickiness, impurities and black mold before recoating. Gjøco Kraftvask has a light matting effect on existent paint and is there for suitable for use before application of new paint.

NOTE: Becomes corrosive on aluminium and metals. Etches glass – windows need to be covered or rinsed clean immediately.

Revised

28.04.2025

Symbols



### Information on composition

<5% cationic surfactants, non-ionic surfactants

### Ingredients

Aqua

Potassiumhydroxide

Propylheptyl ether

C9-11 Pareth-3

Quaternary ammonium compounds, C12-14-alkyl, hydroxyethyl, dimethyl, ethoxylated, chlorides

Sodium metasilicate

Trisodiumdicarboxymethyl alaninate

Tetra Potassium Pyrophosphate

### Technical data

Type: Alkaline cleaning

Specific gravity: 1,07 kg/l

pH value, diluted solution: 13


### Usage data

Application method: Low pressure sprayer, pump sprayer.

Recommended spreading rate: 1 liter washing solution for approx. 15 m<sup>2</sup>.

Mixing ratio: 1:30 (1 litre Kraftvask to 30 litres of water).

Minimum application temperature: >0 °C. Best effect at 20 °C. Should not be applied in direct sunshine.

<b>Directions for use</b>	The surface needs to be dry before application. Apply Gjøco Kraftvask with even movements down to up and make sure that all areas are covered. Avoid waste on dry surfaces. Leave the product on for 2-5 minutes (don't let it dry out). Heavily soiled surfaces should be washed with brush or broom. Use a garden hose and rinse with clean water from top to bottom. High pressure washer can be used but beware that this can damage the woodwork and cause penetration of water. Don't use the product in direct sun. Avoid spraying Gjøco Kraftvask directly on plants. In case of waste, wash with water.
<b>Storage</b>	Screw the top back on when storing to prevent spillage and drying out. The product must be transported and stored upright, dry and frost-free.
<b>Disposal of waste</b>	<p>The product must not be emptied into sewers or into nature, but delivered to an environmental station. Empty, clean, and dry plastic packaging can be delivered as plastic waste.</p> 
<b>Other information</b>	<p>Contains Sodium Metasilicate and lye (Sodium Hydroxide). The solution is cauterizing. Must not be swallowed. Store in a locked compartment and inaccessible for children. Use gloves and eye protection. Avoid contact with eyes, the product contains lye. In case of contact with eyes, wash immediately with plenty of clean water. In case of accident or sickness, immediate medical care is needed. See Safety Data Sheet.</p> <p>Packaging sizes: 1 and 4 litres.</p>
<b>Safety</b>	See separate safety data sheet. Read the information on the packaging.

The information on this data sheet is based on laboratory tests and practical experience. Our products are considered semi-finished products and as the conditions under which the products are used are often beyond our control, we cannot guarantee anything other than the product's quality. The products are delivered in accordance with our general terms and conditions for sales, delivery and service, unless otherwise agreed in writing. We reserve the right to make minor product changes and to change the specified data without prior notice. This data sheet replaces previous editions.

<b>Contact information</b>	<b>Gjøco AS</b> Ørvegen 1160, 6639 Torvikbukt Telephone: +47 712 91 700 E-mail: <a href="mailto:office@gjoco.no">office@gjoco.no</a>
----------------------------	---

