

Produktdatablad

Gjøco Maling og Lakkfjerner



Gjøco Maling og Lakkfjerner effectively removes most types of paint and varnish on many different surfaces. When used on plastic boats and fine wood species (redwood, mahogany, teak, etc.), it is recommended to test on a small area first.

Note: Gjøco Maling og Lakkfjerner will attack fiberglass after the paint/antifouling has dissolved. It has little effect on two-component paints.

Revised 04.03.2025

Symbols



Technical Data

Type:	Paint and varnish remover
Color:	Transparent liquid/paste
Specific Gravity (kg/l):	Approx. 1.1
Application Method:	Brush or roller
Thinner/Cleaning Agent:	Water
Minimum Application Temperature:	0°C, recommended temperature +15 to 20°C
Coverage:	0.5 – 2 m ² /liter (guideline only; varies depending on paint thickness and application)

Instructions for Use

Apply with a brush or roller. Avoid direct sunlight. Depending on the type of paint and varnish, soft wrinkles and bubbles will form after 5-30 minutes and can be removed with brushing, scraping, and rinsing. Best results are achieved at an application temperature of +15 to 20°C.

Storage

Close the packaging tightly after use to prevent spills and drying out. The product should be transported and stored upright, in a dry place, and protected from frost. Avoid storage in direct sunlight.

Waste Disposal

The product must not be poured into the sewer system or into nature, but should be delivered to a designated environmental station.



Additional Information

See the separate safety data sheet. Read the information on the packaging. Packaging size: 1 liter.

The information in this data sheet is based on laboratory testing and practical experience. Our products are considered semi-finished products, and since the conditions under which the products are used are often beyond our control, we can only guarantee the product's quality. The products are delivered in accordance with our general terms of sale, delivery, and service unless otherwise agreed in writing. We reserve the right to make minor product changes and to change the specified data without prior notice. This data sheet replaces previous versions and is automatically void 5 years after the release date.

Contact Information

Gjøco AS

Ørvegen 1160, 6639 Torvikbukt

Telephone: +47 712 91 700

Email: office@gjoco.no

