



## FDV – Management, operation, and maintenance

### Gjøco Oljegrunning



Gjøco Oljegrunning is a slightly thixotropic primer for exterior woodwork, based on penetrating alkyds and oils. It contains film-preserving agents against mildew. Gjøco Oljegrunning is ideal for priming bare exterior wood of spruce and pine. It can also be used on treated wood.

Revised	11.03.2025	
<b>Application Instructions</b>	<b>Substrate:</b>	The surface should be clean and dry, with a minimum temperature of +5 °C
	<b>Application Methods:</b>	Brush. Spraying is not permitted.
	<b>Thinner:</b>	White Spirit.
	<b>Storage:</b>	Store and transport upright, dry, and frost-free, out of reach of children.
	<b>Transport:</b>	Not classified as dangerous goods under applicable regulations.
	<b>Indoor Environment/Emission:</b>	The product is intended for outdoor use.
<b>Technical and Safety Data</b>	A technical data sheet and safety data sheet (SDS/HMS) have been prepared for the product. See <a href="http://www.gjoco.no">www.gjoco.no</a> . VOC: EU limit for the product (category A/e): 700 g/l (2010). The product contains <500 g/l VOC.	
<b>Maintenance</b>	<b>Cleaning:</b>	Typically not applicable, as the product is not used alone and is intended to be painted over.
	<b>Interval:</b>	Cladding treated with oil-based primer should be further treated as quickly as possible. If the primer degrades before painting, the surface must be cleaned and brushed with a wire brush before reapplying the primer.

**Waste Disposal**

Liquid stain should not be poured into sewers or nature but delivered to an approved hazardous waste facility. Empty and dry packaging should be delivered to an approved waste facility. Refer to the regulations for hazardous waste for further information.

**Repairs/Damage**

Repairs and damages should be addressed with the same type of product. Documentation must be provided to confirm it is the same type previously used if other products are employed. Repairs should be carried out to match previous treatments. For repainting or color changes, it is recommended to use the same product as before. Contact the dealer or paint company for advice.

**Surface/Material Information****Painted in color:****Color name:****NCS:****Batch number:****Work performed by:****Date:****Signature:**

The information in this data sheet is based on laboratory tests and practical experience. Our products are considered semi-finished goods, and as conditions of use are often beyond our control, we can only guarantee the product's quality. Products are delivered under our general terms for sale, delivery, and service unless otherwise agreed in writing. We reserve the right to make minor product changes and amend the specified data without prior notice. This data sheet replaces earlier versions and is automatically invalid five years after the publication date.

**Contact Information**

**Gjøco AS**  
Ørvegen 1160, 6639 Torvikbukt  
Phone: +47 712 91 700  
Email: office@gjoco.no

