



FDV – Management, operation, and maintenance

Gjøco Oljegrunning



Gjøco Oljegrunning is a slightly thixotropic primer for exterior woodwork, based on penetrating alkyds and oils. It contains film-preserving agents against mildew. Gjøco Oljegrunning is ideal for priming bare exterior wood of spruce and pine. It can also be used on treated wood.

Revised 10.04.2026

Application Instructions	Substrate:	The surface should be clean and dry, with a minimum temperature of +5 °C
	Application Methods:	Brush. Spraying is not permitted.
	Thinner:	White Spirit.
	Storage:	Store and transport upright, dry, and frost-free, out of reach of children.
	Transport:	Not classified as dangerous goods under applicable regulations.
	Indoor Environment/Emission:	The product is intended for outdoor use.
Technical and Safety Data	A technical data sheet and safety data sheet (SDS/HMS) have been prepared for the product. See www.gjoco.no . VOC: EU limit for the product (category A/e): 700 g/l (2010). The product contains <500 g/l VOC.	
Maintenance	Cleaning:	Typically not applicable, as the product is not used alone and is intended to be painted over.
	Interval:	Cladding treated with oil-based primer should be further treated as quickly as possible. If the primer degrades before painting, the surface must be cleaned and brushed with a wire brush before reapplying the primer.

Waste Disposal

Liquid stain should not be emptied into sewers or into the environment, but delivered to an approved hazardous waste collection point. Empty, clean and dry packaging should be delivered to an approved collection point.



Repairs/Damage

Repairs and damages should be addressed with the same type of product. Documentation must be provided to confirm it is the same type previously used if other products are employed. Repairs should be carried out to match previous treatments. For repainting or color changes, it is recommended to use the same product as before. Contact the dealer or paint company for advice.

Eco-labeling

BREEAM-NOR v6.1
– MAT02: Contains no substances listed under REACH Article 59(10) – the Candidate List and the Norwegian A20 list. See also the product safety data sheet.

Surface/Material Information

Painted in color:

Color name:

NCS:

Batch number:

Work performed by:

Date:

Signature:

The information provided in this data sheet is based on laboratory tests and practical experience. As the conditions under which the products are used are often beyond our control, we cannot guarantee anything other than the quality of the product itself. The products are supplied in accordance with our general terms and conditions of sale, delivery, and service, unless otherwise agreed in writing. We reserve the right to change the stated data without prior notice. Paint may be regarded as a semi-finished product, and the final result depends on factors such as surface preparation, temperature, application method, type of substrate, etc.

Contact Information

Gjøco AS
Ørvegen 1160, 6639 Torvikbukt
Phone: +47 712 91 700
Email: office@gjoco.no

