



FDV – Management, operation, and maintenance

Gjøco Oljemaling



Gjøco Oljemaling is a weather-resistant, thixotropic alkyd paint designed for outdoor use. It is enriched with film-preserving antifungal agents, has a rich consistency, and is easy to apply. Gjøco Oljemaling is suitable for use on new, stained, covered, or previously painted wood surfaces. It can also be used as a topcoat on primed iron, previously painted, cured masonry, and concrete. Additionally, it is suitable for use on pressure-treated, primed materials.

Revised

15.01.2025

Application Instructions

Substrate:

The surface should be clean and dry, with a minimum temperature of 0 °C

Application Methods:

Brush, roller, or spray. Spraying should be performed by professionals.

Thinner:

White Spirit; thinning is usually not necessary.

Storage:

Store and transport upright, dry, and frost-free, out of reach of children.

Transport:

Not classified as dangerous goods under applicable regulations.

Indoor Environment/Emission:

The product is intended for outdoor use.

Technical and Safety Data

A technical data sheet and safety data sheet (SDS/HMS) have been prepared for the product. See www.gjoco.no. VOC: EU limit for the product (category A/e): 300 g/l (2010). The product contains <300 g/l VOC.

Maintenance

Cleaning:

For annual cleaning, Gjøco Husvask is recommended. If surfaces are contaminated with mildew, they can also be treated with Gjøco Sopp- og grønskefjerner. For cleaning prior to repainting, Gjøco Kraftvask is recommended. Follow the product instructions. Newly painted wood surfaces should not be washed until 3–4 weeks after application.

Interval:

The paint film naturally degrades due to weather exposure and will vary depending on local conditions. Repainting should therefore be done as needed, when the film appears matte and worn. Weather-exposed walls are more vulnerable to the elements and typically

require more frequent repainting than the rest of the building

Waste Disposal

Liquid stain should not be poured into sewers or nature but delivered to an approved hazardous waste facility. Empty and dry packaging should be delivered to an approved waste facility. Refer to the regulations for hazardous waste for further information.



Repairs/Damage

Repairs and damages should be addressed with the same type of product. Documentation must be provided to confirm it is the same type previously used if other products are employed. Repairs should be carried out to match previous treatments. For repainting or color changes, it is recommended to use the same product as before. Contact the dealer or paint company for advice.

Surface/Material Information

Painted in color:

Color name:

NCS:

Batch number:

Work performed by:

Date:

Signature:

The information in this data sheet is based on laboratory tests and practical experience. Our products are considered semi-finished goods, and as conditions of use are often beyond our control, we can only guarantee the product's quality. Products are delivered under our general terms for sale, delivery, and service unless otherwise agreed in writing. We reserve the right to make minor product changes and amend the specified data without prior notice. This data sheet replaces earlier versions and is automatically invalid five years after the publication date.

Contact Information

Gjøco AS
Ørvegen 1160, 6639 Torvikbuk
Phone: +47 712 91 700
Email: office@gjoco.no

