

FDV - Management, Operation, and Maintenance

Gjøco Proff Lettsparkel Fin



Proff Lettsparkel Fin is a high-quality lightweight filler for indoor use in dry rooms. The product is easy to apply and sand, and has excellent filling properties. It is suitable for joint and spot filling of gypsum and construction boards. It can also be used for filling plaster and concrete. Ideal for filling in thin layers where a fine and smooth surface is required. When joint filling gypsum boards, paper tape must be used.

Revised:	11.06.2025		
Instructions for Use	Substrate:	The surface must be clean and dry.	
	Type:	Latex copolymer with white dolomite as filler.	
	Application method:	Spray or steel trowel.	
	Cleaning agent:	Water.	
	Thinner:	Normally should not be thinned.	
	Storage:	Store in a dry and frost-free place, out of reach of children.	
	Transport:	Not classified as hazardous goods according to current regulations.	
	Indoor environment / Emissions:	The product emits low levels of emissions.	
Technical Data and Safety Information	A technical data sheet and a safety data sheet (HMS / SDS) have been prepared for the product. See www.gjoco.no.		
Maintenance	Cleaning:	Not applicable. The product is not used on its own.	
	Interval:	Not applicable. The product is not used on its own.	

Wasto	Dispos	a۱
vvasie	DISDOS	a١

Filler must not be emptied into drains or released into nature but must be delivered to an approved hazardous waste disposal facility. Empty, clean, and dry plastic packaging without a handle can be disposed of as plastic waste.





Repairs / Damage

Not applicable. The product is not used on its own.

Treated Surface / Type of Substrate:		
Batch Number:		
Painting Work Performed By:		
Date:		
Signature:		

The information in this data sheet is based on laboratory tests and practical experience. Our products are considered semi-finished goods, and since the conditions under which the product are used are often beyond our control, we can only guarantee the quality of the product itself. The products are supplied in accordance with our general terms and conditions for sales, delivery, and service, unless otherwise agreed in writing. We reserve the right to make minor product changes and to amend the specified data without prior notice. This data sheet replaces previous versions and is automatically void five years after the publication date.

Contact Information

Gjøco AS

Ørvegen 1160, 6639 Torvikbukt, Norway

Phone: +47 712 91 700 Email: office@gjoco.no

