

Product Data Sheet

Gjøco Proff Lettsparkel J



Proff Lettsparkel J is a hand-applied filler specifically designed for joint filling on gypsum boards. It is used indoors on ceilings and walls for joint filling, as well as for filling dents, screw holes, and similar imperfections. Paper joint tapes should be used in conjunction with this product.

Revised 05.12.2024

Symbols



Technical Data


Type:	Latex copolymer with dolomite as filler
Color:	Beige
Density:	Approx. 1.3 kg/l
Solids Content	Approx. 45%
pH:	Approx. 9
Grain Size:	Max 0,2 mm
Application Method:	Steel trowel
Thinner/Cleaning Agent:	Water. Normally not to be diluted.
Consumption:	Broad filling: 1 liter/m ² at 1 mm layer thickness
Drying Time:	Depends on substrate, layer thickness, temperature, and humidity
Touch Dry:	Approx. 8–10 hours
Repainting Interval, Minimum:	Approx. 24 hours
Layer Thickness:	Max. 2 mm
Minimum Application Temperature:	+5°C
Shelf Life:	1 year in unopened packaging

Surface Preparation

The substrate must be clean, dry, grease-free, and free of loose particles. Glossy or contaminated surfaces should be cleaned with Gjøco Husvask or Gjøco Interiørvask.

Application

Apply using a steel trowel. Sanding should be done with fine sandpaper (grit 100–120). Filled surfaces should be primed before wallpapering.

Storage	Seal the lid tightly when storing the filler to prevent spillage and drying out. Transport and store upright, in dry and frost-free conditions.
Waste Disposal	Do not dispose of filler or washing water in sewers or nature. Deliver to an approved hazardous waste facility. Empty, clean, and dry plastic packaging can be disposed of as plastic waste. 
Additional Information	Store in a dry, frost-free location, away from direct sunlight. Unopened packaging can be stored for 12 months. It may remain usable after 12 months; check consistency and smell. Packaging size: 3L and 10L.
Safety	Refer to the dedicated safety data sheet. Read the information on the packaging. Use eye protection when sanding large areas.

The information on this data sheet is based on laboratory tests and practical experience. Our products are considered semi-finished goods, and since conditions of use are often beyond our control, we can only guarantee the product's quality. Products are supplied according to our general terms of sale, delivery, and service unless otherwise agreed in writing. We reserve the right to make minor product changes and update the stated data without prior notice. This data sheet supersedes earlier versions.

Contact Information

Gjøco AS
Ørvegen 1160, 6639 Torvikbukt
Phone: +47 712 91 700
Email: office@gjoco.no

