

Product Data Sheet

Gjøco Proff Lettsparkel Medium



Proff Lettsparkel Medium is a high-quality filler designed for indoor use in dry rooms. The product is easy to apply and sand, offering excellent filling capacity. It is suitable for spot repairs and full-surface leveling of gypsum, concrete, lightweight concrete, and previously painted surfaces. Ideal for use under wallpaper.

Revised 05.12.2024

Symbols



Technical Data

Type:	Latex copolymer with dolomite and aluminum silicate as fillers
Color:	White
Density:	Approx. 1.3 kg/l
Solids Content	Approx. 58%
pH:	Approx. 9
Grain Size:	Max 0,2 mm
Application Method:	Steel trowel, steel blade, or machine
Thinner/Cleaning Agent:	Water. Normally not to be diluted.
Consumption:	Broad filling: 1 liter/m ² at 1 mm layer thickness
Drying Time:	Depends on substrate, layer thickness, temperature, and humidity
Touch Dry:	Approx. 0,5 hours
Repainting Interval, Minimum:	Approx. 24 hours
Layer Thickness:	Max. 3 mm
Minimum Application Temperature:	+5°C
Shelf Life:	1 year in unopened packaging

Surface Preparation

The substrate must be clean, dry, grease-free, and free of loose particles. Glossy, painted surfaces should be cleaned with Gjøco Husvask or Gjøco Interiørvask and lightly sanded. Unevenness should be removed by sanding. For joint filling with paper tape on new gypsum boards, it is recommended to use Proff Lettsparkel Fin or Proff Lettsparkel J.

Application

Proff Lettsparkel Medium should be applied with a trowel, steel blade, or machine. It is important that the filler is completely dry between each application.

Recommended consumption: Depending on the substrate, approx. 1 m²/liter at a 1 mm thickness. Working temperature: The substrate should be above +10°C during application. Sanding should be done with fine sandpaper (grit 100–120). Filled surfaces should be primed before wallpapering.

Storage

Seal the lid tightly when storing the filler to prevent spillage and drying out. Transport and store upright, in dry and frost-free conditions.

Waste Disposal

Do not dispose of filler or washing water in sewers or nature. Deliver to an approved hazardous waste facility. Empty, clean, and dry plastic packaging can be disposed of as plastic waste.

**Additional Information**

Store in a dry, frost-free location, away from direct sunlight. Unopened packaging can be stored for 12 months. It may remain usable after 12 months; check consistency and smell. Packaging size: 400L, 3L and 10L.

Safety

Refer to the dedicated safety data sheet. Read the information on the packaging. Use eye protection when sanding large areas.

The information on this data sheet is based on laboratory tests and practical experience. Our products are considered semi-finished goods, and since conditions of use are often beyond our control, we can only guarantee the product's quality. Products are supplied according to our general terms of sale, delivery, and service unless otherwise agreed in writing. We reserve the right to make minor product changes and update the stated data without prior notice. This data sheet supersedes earlier versions.

Contact Information

Gjøco AS
Ørvegen 1160, 6639 Torvikbukt
Phone: +47 712 91 700
Email: office@gjoco.no

