

FDV – Management, Operation and Maintenance

Gjøco Supermatt Rom 01



Gjøco Supermatt Rom 01 is a water-thinnable, matt acrylic wall paint that provides depth of color and a beautiful, calm finish without sheen. It is used on walls made of materials such as building boards, paintable wallpaper, plaster, concrete, and filler.

Revised

07.01.2025

Usage Instructions	Substrate:	Ensure the surface is clean and dry, with a minimum temperature of +10°C
	Application Method:	Brush, roller, or spray. Spraying should be done by professionals.
	Thinner:	Water. The lacquer generally does not require thinning.
	Storage:	Store and transport upright, dry, frost-free, and out of reach of children.
	Transport:	Not classified as hazardous goods under applicable regulations.
	Indoor Environment/Emissions	The product emits low emissions.

Technical and Safety Data A technical data sheet and safety data sheet (SDS / HSE data sheet) have been prepared for the product. See www.gjoco.no. VOC: The EU limit value for the product (category A/i): 30 g/l (2010). The product contains <1 g/l VOC.

Maintenance

Cleaning: For cleaning before repainting, it is recommended to use an alkaline cleaning agent such as Gjøco Interiør vask or Husvask. Follow the instructions on the product. Newly painted surfaces should not be cleaned until after 3-4 weeks. It is advisable to use microfiber cloths with clean water or mild soapy water. The temperature of the wash water should not exceed +40°C, and the pH should not exceed 9. The use of cleaning agents with abrasives may damage the surface. Cleaning should be done in a way that avoids streaks. Cleaning should be performed as needed. The paint film wears more quickly with heavy cleaning use.

Intervals:

The paint film is affected by mechanical impact and wears according to the level of stress. Maintenance intervals will therefore vary based on need.

Waste Management

Liquid paint should not be poured into the sewage system or nature, but should be delivered to an approved hazardous waste disposal facility. Empty, clean, and dry plastic packaging without handles can be disposed of as plastic waste.



Repairs/Damage

Repairs and damages should be addressed using the same type of product. If other products are used, it must be documented that they are of the same type previously applied. Repairs should be carried out in a way that does not deviate from previous treatments. For repainting or color changes, it is recommended to use the same product as previously applied. Contact your dealer or a painting company for assistance.

Environmental Certification

The product is approved by Environmental Certification Norway and meets the requirements for the Swan environmental label.



The product has been tested according to the testing requirements set by BREEAM-NOR. The product meets BREEAM-NOR HEA 02. Gjøco Supermatt Room 01 contains no substances on the A20 list.

Treated Surface/Type of Substrate:

.....

Painted in Color:

Color Name:

NCS:

Batch Number:

.....

Painting Performed By:

.....

Date:

.....

Signature:

.....

The information in this data sheet is based on laboratory tests and practical experience. As our products are semi-finished goods, and usage conditions often fall outside our control, we only guarantee the product's quality. Products are delivered under our general terms of sale, delivery, and service unless otherwise agreed in writing. Minor product changes and data updates may occur without notice. This data sheet replaces previous editions and is automatically invalidated five years after its issue date.

Contact information

Gjøco AS

Ørvegen 1160, 6639 Torvikbukta

Phone: +47 712 91 700

Email: office@gjoco.no

