



## FDV – Management, operation, and maintenance

### Gjøco Takdekk



Gjøco Takdekk is an acrylic paint for outdoor treatment of roofs made of corrugated sheet metal, galvanized plates, aluminum, steel, roof tiles, asbestos cement, etc. It is not suitable for use on asphalt shingles or certain types of asbestos cement (super, flat). Gjøco Takdekk has good weather resistance and extends the lifespan of the roof by many years.

Revised

15.08.2025

<b>Application Instructions</b>	<b>Substrate:</b>	The surface must be clean and dry, with a minimum temperature of +5 °C.
	<b>Application Methods:</b>	Brush, roller, or spray. Spraying should be carried out by professionals.
	<b>Thinner:</b>	Water, thinning is usually not necessary.
	<b>Storage:</b>	Store and transport upright, dry, and frost-free, out of reach of children.
	<b>Transport:</b>	Not classified as dangerous goods under applicable regulations.
	<b>Indoor Environment/Emission:</b>	The product is intended for outdoor use.
<b>Technical and Safety Data</b>	A technical data sheet and safety data sheet (SDS/HMS) have been prepared for the product. See <a href="http://www.gjoco.no">www.gjoco.no</a> . VOC: EU limit for the product (category A/e): 40 g/l (2010). The product contains <40 g/l VOC.	
<b>Maintenance</b>	<b>Cleaning:</b>	For annual cleaning, Gjøco Husvask or Kraftvask is recommended. Algae and moss can be removed with Gjøco mose- og algefjerner. Rusted surfaces should be sandblasted to SA 2 ½ or brushed to SA 2. Untreated aluminum roofs and galvanized plates must be primed with Gjøco Metal Primer before applying Gjøco Takdekk. Rusty metal roofs should be primed with Gjøco AntirustPrimer after the rust has been removed, before further treatment with Gjøco Takdekk. Roof tiles should be primed with Gjøco Primer for Masonry and Concrete. Follow the instructions on the product

**Interval:**

The paint film naturally breaks down due to weather exposure and will vary based on local conditions. Repainting must therefore be done as needed, when the film appears dull and worn. The weather wall(s) are more exposed to the weather and typically require more frequent repainting than the rest of the building.

**Waste Disposal**

Liquid paint must not be emptied into sewers or into nature, but must be delivered to an approved hazardous waste collection point. Empty, clean and dry plastic packaging without handle, can delivered as plastic waste.

**Repairs/Damage**

Repairs and damages should be addressed with the same type of product. Documentation must be provided to confirm it is the same type previously used if other products are employed. Repairs should be carried out to match previous treatments. For repainting or color changes, it is recommended to use the same product as before. Contact the dealer or paint company for advice.

**Surface/Material Information****Painted in color:****Color name:****NCS:****Batch number:****Work performed by:****Date:****Signature:**

The information in this data sheet is based on laboratory tests and practical experience. Our products are considered semi-finished goods, and as conditions of use are often beyond our control, we can only guarantee the product's quality. Products are delivered under our general terms for sale, delivery, and service unless otherwise agreed in writing. We reserve the right to make minor product changes and amend the specified data without prior notice. This data sheet replaces earlier versions and is automatically invalid five years after the publication date.

**Contact Information**

**Gjøco AS**  
Ørvegen 1160, 6639 Torvikbukt  
Phone: +47 712 91 700  
Email: office@gjoco.no

