

Product datasheet

Gjøco Taklakk



Gjøco Taklakk is a glossy roof paint with penetrating oils and additives that prevent rust formation. Gjøco Taklakk can be used directly on old and rusty corrugated iron roofs after cleaning. It provides a durable and water-resistant surface that will extend the life of the roof by many years.

Revised 08.10.2025

Symbols



Technical data

Type:	Alkyd oil-based
Color:	Black
Gloss:	Gloss 50-60
Flash point:	62 °C
Specific gravity:	1.1 kg/l
Solid content:	Approx. 61 volum%
Application method:	Brush or spray. Spraying is recommended to be done by professionals.
Thinner / cleaning agent:	White Spirit
Film thickness, wet:	90 mikrometers
Film thickness, dry:	40 mikrometers
Recommended spreading rate:	10 m ² /liter, depending on the substrate.
Recommended data for airless spray:	
Nozzle tip:	0.46 mm (0.018")
Spray angle degrees:	65°–80°
Pressure at nozzle:	15–18 MPa (150–180 kg/cm ²)
	The choice of nozzle, fan angle, and pressure must be adjusted to the specific spray equipment and substrate.
Drying time (23 °C, 50 % R.H.):	Depends on temperature, humidity, wind and film thickness.
Dust dry:	6 hours
Interval between coats, minimum:	8 hours
Minimum application temperature:	+5 °C Low temperatures may extend drying time. Do not paint if there is a risk of dew.

Pretreatment	The substrate must be clean and dry, and free of grease and contamination. Remove grease, contamination, loose rust and paint. Wash with Gjøco Husvask or Gjøco Kraftvask and high-pressure spray. Follow the instructions on the packaging. Rinse well with clean water. Gjøco Taklakk can be applied directly to the substrate. If you want extra protection against rust, you can prime it with Gjøco Antirustprimer.
Directions for use	Gjøco Taklakk should not normally be thinned. Stir well before use. Different batch numbers are mixed before use, to avoid gloss and color differences. Dew on a semi-dry surface can cause matte streaks. Matte streaks can also occur when drying at low temperatures and high humidity. Sun on a wet or semi-dry surface can cause blistering. Control the spray mist when spraying.
Storage	Seal the lid tightly when storing paint to prevent spillage and drying. The paint must be transported and stored upright, dry and frost-free.
Disposal of waste	Liquid paint should not be emptied into sewers or into the environment, but delivered to an approved hazardous waste collection point. Empty, clean and dry packaging should be delivered to an approved collection point. 
Other information	Stir well before use. The contents of cans with different batch numbers are mixed before use to avoid differences in gloss and color. Dew on a semi-dry surface can cause dull streaks. Dull streaks can also occur when drying at low temperatures and high humidity. Sun and high heat on a wet or semi-dry surface can cause blistering. Therefore, avoid application in sunlight and in strong heat. Package sizes: 10 liters.
Safety	See separate safety data sheet. Read the information on the packaging. EU limit value for this product (kat. A/d): 400 g/l (2010). This product contains: <400 g/l VOC.

The information on this data sheet is based on laboratory tests and practical experience. Our products are considered semi-finished products and as the conditions under which the products are used are often beyond our control, we cannot guarantee anything other than the product's quality. The products are delivered in accordance with our general terms and conditions for sales, delivery and service, unless otherwise agreed in writing. We reserve the right to make minor product changes and to change the specified data without prior notice. This data sheet replaces previous editions.

Contact information

Gjøco AS
 Ørvegen 1160, 6639 Torvikbukt
 Telephone: +47 712 91 700
 E-mail: office@gjoco.no

