

Product datasheet

Gjøco Teakolje G1



Gjøco Teakolje G1 is a colorless, alkyd-based special impregnation with excellent penetrating properties. It is used as an impregnating oil for wooden boats, garden furniture, garage doors, and other details made of teak and other hardwoods. Gjøco Teakolje G2 is used as a topcoat where a glossier finish with increased durability is desired.

Revised 16.05.2025

Symbols



Technical data


| | |
|----------------------------------|---|
| Type: | Alkyd-based wood impregnation |
| Color: | Transparent |
| Flash point: | Approx. 35 °C |
| Density: | 0.84 kg/l |
| Solids content: | Approx. 20% by volume |
| Application method: | Brush |
| Thinner / Cleaning agent: | White spirit or turpentine |
| Recommended coverage: | 5 m ² /liter, depending on the substrate |
| Drying time (23 °C, 50% R.H.): | |
| Dust dry: | 3 hours |
| Recoating interval, minimum: | Wet-on-wet |
| Minimum application temperature: | +5 °C |

Pretreatment

Weathered, gray wood must be wire brushed or sanded down to fresh wood before treatment. Previously treated surfaces should be scraped and brushed clean of loose particles. Dirty and/or fungus-affected surfaces should be cleaned with Gjøco Kraftvask.

Directions for use

Apply 2–4 wet-on-wet coats to new or previously treated wood until the wood is saturated with oil. Wipe off excess oil in the direction of the grain using a lint-free cloth. If desired, the first coat on new wood can be thinned with Gjøco Ren Terpentin. Gjøco Teakolje G2 is used as a topcoat where a glossier finish with increased durability is desired.

| | |
|--------------------------|---|
| Storage | Seal the lid tightly when storing paint to prevent spills and drying out. The product should be transported and stored upright, in a dry, frost-free environment. |
| Disposal of waste | Liquid paint and wash water must not be poured into drains or released into nature, but should be delivered to a hazardous waste disposal station.  |
| Other information | The product must be stored in accordance with national regulations. The surface must be clean and dry before applying Gjøco Teak Oil G1. Stir well before use. Multiple coats and low temperatures will extend the drying time. Gjøco Teak Oil G1 is a thin oil that does not form a surface film. Therefore, more than one treatment per year may be necessary. For more detailed information, refer to the safety and technical data sheets at gjoco.no . Packaging sizes: 0.75 and 3 liters |
| Safety | See separate safety data sheet. Read the information on the packaging. |

The information on this data sheet is based on laboratory tests and practical experience. Our products are considered semi-finished products and as the conditions under which the products are used are often beyond our control, we cannot guarantee anything other than the product's quality. The products are delivered in accordance with our general terms and conditions for sales, delivery and service, unless otherwise agreed in writing. We reserve the right to make minor product changes and to change the specified data without prior notice. This data sheet replaces previous editions.

Contact information
Gjøco AS
Ørvegen 1160, 6639 Torvikbukt, Norway
Telephone: +47 712 91 700
E-mail: office@gjoco.no

