

Product Data Sheet

Gjøco Teakolje G2 Toppstrøk



Gjøco Teak Oil G2 Topcoat is a colorless, alkyd-based special impregnation that provides a glossy and fine surface. Used as a topcoat for boats above the waterline, garden furniture, garage doors and other details made of teak and other hardwoods. Can be used as a topcoat in a system with Gjøco Teak Oil G1.

Revised 18.03.2026

Symbols



Technical data

| | |
|----------------------------------|-----------------------------------|
| Type: | Alkyd oil-based wood impregnation |
| Color: | Transparent |
| Specific gravity: | 0.86 kg/l |
| Solid content: | Approx. 31 volum% |
| Application method: | Brush, roller or spray. |
| Thinner / cleaning agent: | White spirit or turpentine. |
| Recommended spreading rate: | 5-10 m ² /liter |
| Drying time (23 °C, 50 % R.H.): | |
| Dust dry: | Approx. 3-4 hours |
| Interval between coats: | 4 hours |
| Minimum application temperature: | +5 °C |

Pretreatment

The substrate must be clean and dry. Grease and contamination must be removed with Gjøco Kraftvask. Surfaces affected by fungus and green mold must be treated with Gjøco Fungus and Green Mold Remover. Allow to dry before further treatment. Smooth and hard substrates must be sanded with P60-P80 for better adhesion. Loose varnish and worn wood must be removed by scraping. Bare wood must be primed with Gjøco Teak Oil G1 wet-on-wet until the wood is saturated. The surface must be lightly sanded before applying Gjøco Teak Oil G2 Top Coat.

Directions for use

Gjøco Teak Oil G2 Top Coat is stirred well and applied to the substrate with a brush. Apply 3-5 coats as needed.

Storage

Close the lid tightly when storing paint to prevent spillage and drying. The paint must be transported and stored upright, dry and frost-free.

| | |
|--------------------------|--|
| Eco-labeling | BREEAM-NOR v6.1 – MAT02: Contains no substances listed under REACH Article 59(10) – the Candidate List and the Norwegian A20 list. See also the product safety data sheet. |
| Disposal of waste | Liquid oil and washing water must not be emptied into sewers or into nature, but must be delivered to an environmental station.  |
| Other information | The product must be stored in accordance with national regulations. The packaging must be kept tightly closed and stored dry at a constant temperature. Packaging sizes: 0.75 and 3 liters. |
| Safety | See separate safety data sheet. Read the information on the packaging. |

The information provided in this data sheet is based on laboratory tests and practical experience. As the conditions under which the products are used are often beyond our control, we cannot guarantee anything other than the quality of the product itself. The products are supplied in accordance with our general terms and conditions of sale, delivery, and service, unless otherwise agreed in writing. We reserve the right to change the stated data without prior notice. Paint may be regarded as a semi-finished product, and the final result depends on factors such as surface preparation, temperature, application method, type of substrate, etc.

Contact information
Gjøco AS
 Ørvegen 1160, 6639 Torvikbukta
 Telephone: +47 712 91 700
 E-mail: office@gjoco.no

