

Product datasheet

Gjøco Terpentin



Gjøco Terpentin is a vegetable solvent extracted from pine trees for solvent-based products. Terpentin is a traditional solvent with good penetration into wood, which is used, among other things, when impregnating wooden boats. Can be mixed with e.g. linseed oil and tar for a good impregnation. Can also be used as a thinner for artists' paints and porcelain paint, which are not soluble in water.

Revised 12.12.2024

Symbols



Technical data

Type:	Vegetable turpentine
Color:	Clear
Specific gravity:	Approx. 0.86 kg/l
Flash point:	>60 °C

Storage

Screw the top back on when storing to prevent spillage and drying out. The product must be transported and stored upright, dry and frost-free.

Disposal of waste

The product should not be emptied into sewers or into nature, but delivered to a waste disposal station.



Other information

Packaging sizes: 1, 4 and 200 litres

Safety

See separate safety data sheet. Read the information on the packaging.

The information on this data sheet is based on laboratory tests and practical experience. Our products are considered semi-finished products and as the conditions under which the products are used are often beyond our control, we cannot guarantee anything other than the product's quality. The products are delivered in accordance with our general terms and conditions for sales, delivery and service, unless otherwise agreed in writing. We reserve the right to make minor product changes and to change the specified data without prior notice. This data sheet replaces previous editions.

Contact information

Gjøco AS
 Ørvegen 1160, 6639 Torvikbuk
 Telephone: +47 712 91 700
 E-mail: office@gjoco.no

